1271

SAT. 12 JUL 1902

Received at London Office

3 Decks. ~~IRON OR~~ STEEL STEAMER.

State if Report is also sent on the Machinery of the Vessel do

Date of completion of report 11th July 1902 Port of 3rd Sep 1901 Belfast No. 54358

Survey held at Londonderry Date, First Survey 3rd Sep 1901 Last Survey 10th June 1902

On the S.S. Barone Edmondo Vaj Rig Schooner

THREE DECKED VESSEL.

CLASS 100 A.1.

TONNAGE under Tonnage Deck	2634.06
Do. between Tonnage Dk. and 3rd and 4th Dk.	
Total under Upper Dk.	
Do. of Poop	82.96
Do. of Bridge House	
Do. of Forecastle	38.07
Do. of Houses on Dk.	70.73
Do. of excess of Hatchways	26.46
Do. above Crown of Engine Room	41.47
Gross Tonnage	2893.75
Less Crew Space	64.92
Above Crown of Engine Room	41.47
ALLOWANCE FOR FEES	2787.36
Engine Room	926.00
Navigation Spaces	80.61
Under Tonnage (Net on Beam)	1887.14

	Feet.	Inches.
Half Breadth (moulded)	22.87	
Depth from upper part of Keel to top of Upper Deck Beams (with the normal round up of beam)	24.87	
Girth of Half Midship Frame (as per Rule)	43.25	
	90.99	
deduct 7 feet	7.00	
1st Number	83.99	
Length on deck from after part of stem to fore part of stern post	323.2	
2nd Number	27145	
Proportions—Breadth to Length	7.06	
Depth to Length—Upper Deck to top of Keel	12.99	
Main Deck ditto		

Master

Year of appointment (1) As Master in service of owner of present vessel:—18 (2) As Master of this vessel 18

Built at Londonderry

When built 1901-2 Launched 4th June 1902

By whom built Londonderry S.B. Co Ltd.

Owners Eredia Matteo Premuda & Co.

Managers (Where necessary to be entered in Reg. Book.)

Residence Lussinpiccolo Austria

Port belonging to Lussinpiccolo

Destined Voyage Glasgow for Mach.y If Surveyed while Building Afloat, ~~or in Dry Dock~~ Yes

	Feet.	Inches.		Feet.	Inches.		Feet.	Inches.	
LENGTH on Deck for Rule	323	2½	**BREADTH**— Moulded	45	9	**DEPTH, ACTUAL**—Top of Floors to top of Upper Dk. Beams	21	4	No. of Decks with flat laid One
						Do. do. do. do. Main Dk. Beams			No. of Tiers of Beams One

Dimensions of Ship per Register, Length 324.0 breadth 46.0 depth 21.3. Moulded depth, ft. 23 ins. 11 To Upper Dk. Round of Upper Dk. Beam, Actual 11½ ins.

FRAMING.	Inches in Ship	Inches in Ship.	8ths or 20ths in Ship.	Inches per Rule Or as Approved	Inches per Rule Or as Approved	8ths or 20ths per Rule Or as Approved
KEEL, ~~double or single~~ Bars for ⅜ length amidships	8½	3½	11	8½	3½	11
for ½ at each end	8½	3½	10	8½	3½	10
In way of Double Bottoms at Solid Floors	3½	3½	8-7	3½	3½	8-7
" " at intermdt. Bkts.						
Depth of Frames from moulding edge to bding edge, all fore and aft	24			24		
KEELSON OR FRAME, Angles						
CENTRE GIRDER, depth of girder	8½			8½		
FLOORS, depth and thickness of Floor Plate at mid-line for ⅜ length amidships						
In way of Engines and Boilers						
Thickness at the ends of vessel						
Depth at ¾ the half breadth, as per Rule						
Height extended at the Bilges						
FRAMES & BRACKETS in **Cell Dble Bottoms**	42		8	42		8
" Distance apart	24			24		
MIDSHIP GIRDER, in Double bottom, depth and thickness	42		10-8	42		10-8
" Angles, Top	4	4	9-8	4	4	9-8
" " Bottom	6½	4	9-8	6½	4	9-8
SIDE GIRDERS, number on each side & thickness	1		8	1		8
" Angles	3½	3½	7	3½	3½	7
MARGIN PLATE, depth (exclusive of flange) and thickness	34		9	32		9
" Angles to Outside Plating	4	4	9	4	4	9
BOTTOM PLATING, breadth and thickness of **Middle Line Strake**	36		10-8	36		10-8
" " in Engine and Boiler space			10-11			10-11
" " Remainder in Holds			8			8
Shelf, Upper Deck, ~~Single Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	8½	3½	11	8½	3½	11
Angles on upper edge						
Average space	24			24		
Shelf, Middle Deck, Single Angle, Bulb Angle, Plate or Tee Bulb						
Angles on upper edge						
Average space						
Shelf, Lower Deck, Single Angle, Bulb Angle, Plate or Tee Bulb						
Angles on upper edge						
Average space						
Shelf, Hold, or Orlop, Plate or Tee Bulb						
Angles on upper edge						
Average space						
BEAMS, Poop Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	6	3	8	6	3	8
Angles on upper edge						
Average space	24			24		
BEAMS, Bridge Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	7	3	9	7	3	9
Angles on upper edge						
Average space	24			24		
BEAMS, Forecastle Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	7	3	9	7	3	9
" Angles on upper edge						
" Average space	24			24		
PILLARS, In 'tween Deck, size and spacing	2¾	opposd	48	2¾	opposd	48
" " **Hold** " "	4¼	"	"	4¼	"	"
" **Quarter 'tween Dks.,** " "						
" " **in Hold** " "						
WEB-FRAMES, In Fore Body, No. and spacing	10	6 frames		10	6 frames	
" " " brdth. & thickness	20		8	20		8
" No of Side Stringers " "	3			3		
WEB-FRAMES, In E. & B. Space, No. & spacing	3	6&5 frames		3	6&5 frames	
" " " brdth. & thickness	20		8	20		8
WEB-FRAMES, In After Body, No. and spacing	7	6 frames		7	6 frames	
" " " brdth. & thickness	20		8	20		8
" No. of Side Stringers " "	3			3		
" Size of Angles ~~or Tee Bars~~ to **Web-Frames**	6	4	12	6	4	12
BRACKET PLATES to Stringers between Web Frames, depth and thickness	14		8	14		8

FORGINGS or CASTINGS.	Inches in Ship.	Inches per Rule. Or as Approved.
KEEL, Bar or Side Plates, depth and thickness	Flat plate	
STEM, moulding and thickness	10½×2¾	10½×2¾
STERN-POST for Rudder do. do.	11×6	11×6
" for Propeller	11×6	11×6
MAIN PIECE of **Rudder,** diameter at head	8½	8½
" " do. at heel	7⅞×5¼	7⅞×5¼ as appd.

RUDDER, how constructed Cast steel frame Single plate

Can the Rudder be unshipped afloat? Yes.

KEELSONS & STRINGERS.	Inches in Ship.	Inches in Ship.	8ths or 20ths in Ship.	Inches per Rule Or as Approved	Inches per Rule Or as Approved	8ths or 20ths per Rule Or as Approved
CENTRE LINE KEELSON, Vertical Plate above floors, Through Plate, or Intercostal Plate						
" Rider Plate						
" Bulb Plate to Intercostal Keelson						
" Horizontal Plates on Floors						
" Angles						
SIDE KEELSON, Angles						
" Bulb or Plate above floors, for lng.						
" Intercostal Plate, for length						
" Attached to outside Plating with Angle						
BILGE KEELSON, Angles						
" Bulb or Plate above floors, for lng.						
" Intercostal Plate for length						
" Attached to outside Plating with Angle						
BILGE STRINGER Angles						
" Bulb Plate for length						
" Intercostal Plate for length						
" Attached to outside Plating with Angle	See web frames					
SIDE STRINGER Angles ~~face~~	6	4	12	6	4	12
" Bulb or Intercostal Plate, for ~~full~~ lng.	20		8	20		8
" Attached to outside plating with Angle	3½	3½	9-8	3½	3½	9-8
Upper Deck Stringer Plates, br'dth & thickness	46	½	12	46	½	12
" Angle on ditto	4×4		9-8	4×4		9-8
" Tie Plates fore and aft, outside Hatchways	4½×4½		10-9	4½×4½		10-9
" Deck.* ~~Iron or~~ Steel, for ~~full~~ lng.			7-6			7-6
" Wood Deck. Material & thickness						
Middle Deck Stringer Plate, br'dth & thickness						
" Angles on ditto, No.						
" Tie Plates outside Hatchways						
" Diagonal Tie Plates on Bms., No. of prs.						
" Deck.* Iron or Steel, for lng.						
" Wood Deck. Material & thickness						
Lower Deck Stringer Plate, br'dth & thickness						
" Angles on ditto, No.						
" Tie Plates, outside Hatchways						
" Deck.* Material and thickness						
Hold, or Orlop Stringer Plate, br'dth & thckn's						
" Angles on ditto, No.						
" Tie Plates outside Hatchways						
" Deck. Material and thickness						
Poop Deck Stringer Plate, breadth & thickness	30		6	30		6
" Angle on ditto	3½×3½		7	3½×3½		7
" Tie Plates						
" Deck. Material and thickness Steel			6			6
Bridge Deck Stringer Plate, br'dth & thickness	35		8	35		8
" Angle on ditto	3½×3½		8	3½×3½		8
" Tie Plates						
" Deck. Material and thickness Steel			6			6
Forecastle Deck Stringer Plate, b'dth & th'kns	32		6	30		6
" Angle on ditto	3½×3½		7	3½×3½		7
" Tie Plates Plated at centre			8			
" Deck. Material and thickness P.P.	5×3			5×3 P.P.		

* If Iron or Steel Deck, state if whole or part, and if Wood Deck is laid thereon.

BULKHEADS.	Number. In Vessel.	Number. Per Rule.	Thickness.	STIFFENERS. Horizontal Size.	STIFFENERS. Horizontal Spacing	STIFFENERS. Vertical Size.	STIFFENERS. Vertical Spacing	Single or Double Frames.	Height up.
			8ths or 20ths.	Inches.	Inches.	Inches.	Inches.		
W. T. BULKHEADS	5	5	1-6	as appd		4.7×3×$\frac{5}{20}$	30	Dbl	to Dk.
PARTITION "	1		6	with webs and demi-beams					
LONGITUDINAL "									

Are the outside Plates doubled two spaces of Frames in length? Appd. Generally

Are the ~~Sluice Valves and~~ Watertight Doors in efficient working order? not yet fitted

Form No. 1B. 9-96

© 2020 Lloyd's Register Foundation

PLATING.

STRAKES.	AS IN SHIP. AMIDSHIP. Breadth.	AS IN SHIP. AMIDSHIP. Thickness.	AS IN SHIP. FORWARD. Thickness.	AS IN SHIP. AFT. Thickness.	PER RULE OR AS APPROVED. AMIDSHIPS. Breadth.	PER RULE OR AS APPROVED. AMIDSHIPS. Thickness.
	Inches.	16ths or 20ths	16ths or 20ths	16ths or 20ths	Inches.	16ths or 20ths
Flat Plate Keel (If Bar Keel, state Riveting)	36	19	14	14	36	19-13
Garboard or A Strake	54	15	13	12	54	15-12
B "		11	11	9		11-9
C "		11	10	13		11-9
D "		12	9	14		12-9
E "		12	9	14		12-9
F "		12	9	13		12-9
G "		12	9	12		12-9
H "		12	9	12		12-9
J "		12	9	10		12-9
K "		14	9	10		14-9
Sheerstrake L "	44	15	10	10	44	15-10
M "						
N "						
O "						
P "						
Q "						
R "						

State actual thickness in way of Double Bottoms

Write Sheer Strake opposite its corresponding letter.

Doubling of Flat Plate Keel: Increased thickness in lieu

Length and thickness — of Bilges: ; of Sheerstrakes.: do. do. ; of Strake below: do. do.

Poop Sides: ; Bridge Sides: 9 7 7 ; Forecastle Sides: 7 7

RIVETING.

	EDGES. Single or Double.	EDGES. Breadth of Lap.	RIVETS. Diam.	RIVETS. Spacing cr. to cr.	BUTTS. Double or Treble and for what Length.	BUTTS. RIVETS. Diam.	BUTTS. RIVETS. Spacing cr. to cr.	BUTTS. STRAPS. Breadth.	BUTTS. STRAPS. Thickness.	IF LAPPED. Breadth.	IF LAPPED. For what Length.
		Inches.	Inches.	Inches.		Inches.	Inches.	Inches.	16ths or 20ths	Inches.	Feet.
Flat Plate Keel	Dbl.	6	1	4							
Garboard or A Strake		5 1/4	7/8	3 1/16	Dbl.	1	6 1/2	19 1/2	14-12		
B "		"	"	"	Quad	7/8	"			10 1/2	Gall.
C "		"	"	"		"	"			12 1/4	"
D "		"	"	"		"	"			"	"
E "		"	"	"	Dbl.	"	3/5			9	"
F "		"	"	"		"	"			"	"
G "		"	"	"		"	"			"	"
H "		"	"	"		"	"			"	"
J "		"	"	"		"	"			"	"
K "		"	"	"		"	"			"	"
Sheerstrake L "	Dbl.	6	1	4	Quad	1	4	1		14 1/4	"
M "	"	3	7/8	3 1/16	"	"	"			"	"
N "											
O "											
P "											
Q "											
R "											

Doubled at bridge ends

Quarterstrakes

Poop Sides											
Bridge Sides	Dbl.	2 1/2	3/4	3				9 3/4	7/8	5	Gall.
Forecastle Sides	"	2 1/2	7/8	3 3/16				9	6	"	"
	Double strake fwd.	"	"	"				7	6	"	"

Manufacturer's name or trade mark of the Iron or Steel (state process of manufacture of Steel) used for Frames, Floors, Beams, Keelsons, Tie and Stringer Plates, Plating, &c.? Angles, D. Colville Sons, Steel Coy. of Scotland Ld., Lanarkshire Steel Coy, Ltd. Plates, Clyde Bridge Steel Coy, Glasgow Iron or Steel Coy, Ld., Steel Coy. of Scotland Frames Coy. Scotland Yes

Has the Steel been tested as required by the Rules?

Upper Deck (Butts Quad. riveted for 3/4 length amidship.
Stringer Plate (Straps, ~~single, double~~ overlapped for whole length amidship.
Middle Deck (Butts, treble riveted for length amidship.
Stringer Plate (Straps, single, double or overlapped for length amidship.
Butts of Bilge & Side Stringers and Tie Plates, ~~single~~ or double riveted?
Inner Bottom Plating, riveting of **Edges** Dbl. 1-3/8. **Butts** Dbl.
Centre Girder Butts, Dbl. riveted **Keelson Butts,** Dbl. riveted.
Frames, riveted through Plates with 7/8 in. Rivets, about 6/4 apart.
Rivets, state whether Iron or Steel Iron.

FRAMES extend in one length from Centre girder to margin plate & from margin plate to gunwale.
REVERSED FRAMES on floors and frames extend from centre girder to margin plate and in peaks to gunwale.
Bulb angle framing elsewhere.

MASTS, SPARS, &c.

	Material.	Total Length.	Diameter and Thickness. At Partners.	Heel.	Hounds.	Head.	No. of Plates in round.	Angles. Number.	Angles. Size.	Riveting. Seams.	Riveting. Butts.
Lower Masts: Fore	Steel	75. 3	20 x 7/20	16 x 6/20		16 1/2 x 6/20	Two			Dbl.	Dbl. Dbl.
Main	do	66. 2	20 x 7/20	18 x 8/20		16 1/2 x 8/20	do			do.	do.
Mizen											
Bowsprit											

Topmasts, Yards and Remainder of **Spars** Telescopic topmasts P.P.
Rigging, Material and Size, **Shrouds** 2 3/4
Sails, One Suit of fore & aft. Sails, and the following spare sails None
Stays 2 1/4, 2 3/4, 3"

EQUIPMENT No. 31080 LETTER R

ANCHORS.

Number of Certificate.	Anchors.	Weight, Ex. Stock. Cwts.	qrs.	lbs.	Weight of Stock. Cwts.	qrs.	lbs.	Test, per Certificate. Tons.	cwts.	qrs.	lbs.	Weight required by Table 22. Cwts.	qrs.	lbs.	Description of Anchor.	Makers.	Where and when tested and Superintendent.
23545	1st Bower	45	3	14	Stockless			39	15	3	21	45	2	0	Britannia	Not given	4.P.H.T. 19/4/02
23525	2nd "	45	2	0	"			39	11	1	0	45	2	0	Sykes patent.	"	" 14/4/02
23543	3rd "	40	0	21	"			35	16	3	14	39	0	0	50	"	" 19/4/02
	4th "																C.S. Perrins
	Collective weight	131	2	7	Stock							130	0	0			
23579	Stream	11	1	3	2	3	21	13	2	2	0	11	1	0	Iron stock		
23578	Kedge	5	2	14	1	1	24	7	18	1	21	5	2	0		Not given	26/4/02

If Differ, state name of Patentee.

Hammer tested at Stockless Anchor Proving House.

CHAIN CABLES.

Number of Certificate.	Fathoms.	Size.	Test per Certificate. Tons.	Weight of Chain Cable. Supplied.	Per Table 22.	Fathoms and Size per Table 22.	Description.	Makers of Cables.	When and where tested, and Superintendent.
23466	270	1 3/16	94 1/2	518-2-21		270 x 1 5/8	Stud	Not given	4.P.H.T. 24/4/02
	3 fms		67 1/2		511-1-14				C.S. Perrins
Iron Stream or Steel Wire	90	4/4	35			90-4/4			

HAWSERS AND WARPS.

Material.	Fathoms.	Size.	Breaking Test of Steel Wire Towline.	Fathoms and Size per Table 22.
Towline	100	4	33	100-4"
Hawser 2 off	90	2 1/2	18	2 off 90-2 1/2"
Warp 2 off	90	2 1/4	15	2 off 90-2 1/4"

Boats 2 Life and 2 others
Pumps, Number 1 4 1/2" Downton & one
Windlass is Diameter of Barrel 5" peak State whether they are in efficient working order Not tried
Iron patent **Capstan**
Engine Room Skylights.—How constructed? Steel casings
What arrangements for deadlights in bad weather? Steel flaps & glass lights.
Coal Bunker Openings.—How constructed? Steel coamings How are lids secured? Battened Height above deck? 9"
Number of **Scuppers,** and numbers and dimensions of **Freeing Ports, &c.** 6 scuppers & 6 freeing ports 3-0 x 1-10 each side
Ceiling in Holds, thickness and material 2 1/2 W.P. **Ceiling 'tween Decks,** thickness and material
Cargo Hatchways.—How formed? Steel coamings **Hatches,** If strong and efficient? Yes.
State size **No. 1 Hatch** (Forward) 16 x 24 **No. 2 Hatch** 16 x 24 **No. 3 Hatch** 16 x 24 **No. 4 Hatch** 16 x 24
Number of **Web Plates, Shifting Beams** and **Fore** and **Afters** to each Hatch 2 web plates & 3 fore and afters to each hatchway 1 hatch 8 x 6 under bridge house
No. of Breasthooks 10 **No. of Crutches** 3 & deep floors
Bulwarks, height above deck and description 3-8" Steel plates 5/20 thick Main Rail, material and size 6 1/2 x 8/20 bulb angle

The above is a correct description. For THE LONDONDERRY SHIPBUILDING & ENGINEERING Co. Ltd.
Builder's Signature (here only) W.H. Dell Swett Managing Director.
Surveyor's Signature E.J. Shilton
Surveyor to Lloyd's Register of British and Foreign Shipping.

Form No. 1B.

Correspondence.—State dates and initials of letters respecting this case (*Reference should be made to any correspondence connected with this case*) M 22nd July 1902
16 Sep 1901. 23rd Sep 1901. 3rd Oct 1901.

Workmanship. Are the butts of plating planed or otherwise fitted? Planed and lapped.
Is the riveted work properly closed? Yes
Are the liners between the frames and plates solid single pieces? Yes Do the holes for riveting plate to frames, butt straps, or plate to plate, &c., conform well to each other? Yes Are the rivet holes well and sufficiently countersunk in the plate and punched from the faying surfaces? Yes Do any rivets break into or through the seams or butts of plating? A few
Are the butts of Plating, Stringers, &c. properly shifted and strapped? Yes
Have all the upper and weather decks been tested as required by the Rules (Sec. 23, par. 24)? Yes State results of tests Satisfactory
Have all the gutterways been tested as required by the Rules (Sec. 23, par. 25)? Yes State results of tests. Satisfactory

General Remarks (State quality of workmanship, &c.)
This vessel has been built in accordance with the Rules and the approved plans, except with regard to the following items, which remain to be dealt with at Glasgow, where she has been towed to receive her machinery
The workmanship and materials are, so far, good throughout.
To be completed at Glasgow
Engine and Boiler casing, saddle backs etc to complete & rivet
Bridge door to fit to Poop front.
Wash coats, Dwinches to fit.
Steam steering gear to complete
Pumping arrangements & watertight doors to fit and test
Tunnels in after hold to rivet and test
The Glasgow Surveyors have been advised.
The Surveyor should state the Number of Report and Name of any Sister Vessel.

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 27 ft., R.Q.D. or Break — ft., Bridge Dk. 94 ft., F'castle 34 ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated Not joined

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) 1 Dk (Steel) Deep framing and web frames

Official No. Signal Letters
How are the surfaces preserved from oxidation? Inside Portland cement & Paint Outside Paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors Cell Dbs

Where fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,	102	249
Double bottom, under Engines and Boilers,		
Double bottom, if under Engines only,	20	60
Double bottom, if under Boilers only,		
Double bottom, forward,	144	376

Where fitted.	*Length. Feet.	Water Capacity. Tons.
Fore peak tank,		
After peak tank,	10	32
Midship deep tank,		
Other tanks, if fitted,		
(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules Yes.

Order for Special Survey No. 457
Date 12 Sep 1901
No. 31 in builder's yard.

Dates of Surveys held while building:
1901. Sep 3. 18. 26. Oct 7. 14. 17 Nov 4. 12. 28 Dec 12.
1902 Jan 14. 29 Feb 14. Mar 1. 8. 17. 18. Apl 2. 15. 29. May 3. 7. 9.
27 June 3. 10.
Total No. of Visits 26

The amount of Entry Fee £5:0:0 Fees applied for, 11 July 1902
Special Survey Fee £24:13:6 Received by me,
Travelling Expenses £29:19:6 £179-13-0 Pd 14/8/02
4.12.pd £281:7:02. £26.15.8 Pd 26/8/02

Certificate to be sent to The Office

State whether the Vessel has been built under Special Survey Yes
I am of opinion this Vessel should be Classed ✠ 100 A 1 Steel.
With, or without Freeboard, as condition of Class Without

E.J. Shilton
Surveyor to Lloyd's Register of British and Foreign Shipping.

The Surveyors are requested not to write on or below the Committee's Minute.

Committee's Minute TUES. 5 AUG 1902
Character assigned Glasgow 100 A1 Steel outside
+ SMCM, 02
Wash Bgd

Hull Certificate. W. Gibson. 19/8/02

© 2020 Lloyd's Register Foundation
W699-01498