

## REPORT ON MACHINERY.

Port of Glasgow Received at London Office TUES. 29 JUL 1902  
 No. in Survey held at Glasgow Date, first Survey 16 Sept. 01 Last Survey 16 July 1902  
 Reg. Book. 174 on the S.S. Barone Edmondo Vaj (Number of Visits 46)  
 Master Built at Londonderry By whom built Londonderry Ship Co. Ltd. When built 1902  
 Engines made at Glasgow By whom made Hulson & Sons, Ltd. when made 1902  
 Boilers made at do By whom made do when made 1902  
 Registered Horse Power 243 Owners E. M. Premuda Port belonging to do  
 Nom. Horse Power as per Section 28 243 Is Refrigerating Machinery fitted No Is Electric Light fitted No

ENGINES, &c.—Description of Engines Triple Expansion No. of Cylinders 3 No. of Cranks 3  
 Dia. of Cylinders 22½-38-62 Length of Stroke 42" Revs. per minute 70 Dia. of Screw shaft as per rule 13.1 Lgth. of stern bush 4-3  
 Dia. of Tunnel shaft as per rule 11.371 Dia. of Crank shaft journals as per rule 11.936 Dia. of Crank pin 12" Size of Crank webs 7½" Dia. of thrust shaft under collars 12" Dia. of screw 15.0" Pitch of screw 16.0" No. of blades 4 State whether moveable No Total surface 72.5  
 No. of Feed pumps 2 Diameter of ditto 3½" Stroke 24" Can one be overhauled while the other is at work Yes  
 No. of Bilge pumps 2 Diameter of ditto 3½" Stroke 24" Can one be overhauled while the other is at work Yes  
 No. of Donkey Engines 2 Sizes of Pumps (10x12x10)(6x4x6) No. and size of Suctions connected to both Bilge and Donkey pumps  
 In Engine Room 2-3" In Holds, &c. 1-3½"-4-3"-2-3½"

No. of bilge injections 1 sizes 4" Connected to condenser, or to circulating pump Yes Is a separate donkey suction fitted in Engine room & size Yes-3½"  
 Are all the bilge suction pipes fitted with roses Yes Are the roses in Engine room always accessible Yes Are the sluices on Engine room bulkheads always accessible Yes  
 Are all connections with the sea direct on the skin of the ship Yes Are they Valves or Cocks Both  
 Are they fixed sufficiently high on the ship's side to be seen without lifting the stokehold plates Yes Are the discharge pipes above or below the deep water line Above  
 Are they each fitted with a discharge valve always accessible on the plating of the vessel Yes Are the blow off cocks fitted with a spigot and brass covering plate Yes  
 What pipes are carried through the bunkers None How are they protected —  
 Are all pipes, cocks, valves, and pumps in connection with the machinery and all boiler mountings accessible at all times Yes  
 Are the bilge suction pipes, cocks, and valves arranged so as to prevent any communication between the sea and the bilges Yes  
 When were stern tube, propeller, screw shaft, and all connections examined in dry dock Before launch Is the screw shaft tunnel watertight Yes  
 Is it fitted with a watertight door Yes worked from Top platform

BOILERS, &c.—(Letter for record (A)) Total Heating Surface of Boilers 3378 Is forced draft fitted No  
 No. and Description of Boilers Two Single Ended built Working Pressure 180 lbs Tested by hydraulic pressure to 360 lbs  
 Date of test 11.4.02 Can each boiler be worked separately Yes Area of fire grate in each boiler 56.75 No. and Description of safety valves to each boiler 2 Spring loaded Area of each valve 5.9" Pressure to which they are adjusted 185 lbs Are they fitted with easing gear Yes  
 Smallest distance between boilers or uptakes and bunkers or woodwork abt. 12" Mean dia. of boilers 14-3" Length 10-6" Material of shell plates Steel  
 Thickness 3/16" Range of tensile strength 27/32 Are they welded or flanged No Descrip. of riveting: cir. seams A. lap long. seams A. B. straps  
 Diameter of rivet holes in long. seams 1½" Pitch of rivets 9" Lap of plates or width of butt straps 18½"  
 Per centages of strength of longitudinal joint 85.6 Working pressure of shell by rules 180 lbs Size of manhole in shell 16x12  
 Size of compensating ring 31x27 No. and Description of Furnaces in each boiler 3 Fox's Material Steel Outside diameter 44"  
 Length of plain part top Thickness of plates bottom 7/32" Description of longitudinal joint welded No. of strengthening rings —  
 Working pressure of furnace by the rules 186 Combustion chamber plates: Material Steel Thickness: Sides 37/64" Back 9/16" Top 37/64" Bottom 13/16"  
 Pitch of stays to ditto: Sides 8¼x7¾" Back 7¾x7¾" Top 8¼x7¾" If stays are fitted with nuts or riveted heads Nuts inside Working pressure by rules 180  
 Material of stays Iron Diameter at smallest part 2.03" Area supported by each stay 64" Working pressure by rules 190 End plates in steam space: Material Steel Thickness 15/16" Pitch of stays 5½x15" How are stays secured Q. Nuts Working pressure by rules 180 Material of stays Iron  
 Diameter at smallest part 5.6" Area supported by each stay 2.32" Working pressure by rules 180 Material of Front plates at bottom Steel  
 Thickness 3/4" Material of Lower back plate Steel Thickness 3/4" Greatest pitch of stays 12½" Working pressure of plate by rules 180  
 Diameter of tubes 3½" Pitch of tubes 4 3/4" Material of tube plates Steel Thickness: Front 3/4" Back 3/4" Mean pitch of stays 9½"  
 Pitch across wide water spaces 14" Working pressures by rules 183 Girders to Chamber tops: Material Iron Depth and thickness of girder at centre 7¾x1¾" Length as per rule 2.9½" Distance apart 7¾" Number and pitch of Stays in each 2-8½"  
 Working pressure by rules 195 lbs Superheater or Steam chest; how connected to boiler None Can the superheater be shut off and the boiler worked separately — Diameter — Length — Thickness of shell plates — Material — Description of longitudinal joint — Diam. of rivet holes — Pitch of rivets — Working pressure of shell by rules — Diameter of flue — Material of flue plates — Thickness —  
 If stiffened with rings — Distance between rings — Working pressure by rules — End plates: Thickness — How stayed —  
 Working pressure of end plates — Area of safety valves to superheater — Are they fitted with easing gear —



**DONKEY BOILER**— No. 1 Description Cylindrical Multitubular  
 Made at Glasgow By whom made Hutton & Sons Ltd When made 1902 Where fixed Main Deck  
 Working pressure 80 lb tested by hydraulic pressure to 160 lb No. of Certificate 6226 Fire grate area 22.7 Description of safety valves Spring loaded  
 No. of safety valves 2 Area of each 4.9 Pressure to which they are adjusted 80 lb If fitted with easing gear Yes If steam from main boilers can enter the donkey boiler No Dia. of donkey boiler 8'-6" Length 8'-0" Material of shell plates Steel Thickness 5/8" Range of tensile strength 27/30 Descrip. of riveting long. seams T. R. Lap Dia. of rivet holes 13/16" Whether punched or drilled Drilled Pitch of rivets 3 1/4"  
 Lap of plating 5 3/4" Per centage of strength of joint 81.5 Rivets 7.5 Thickness of shell crown plates — Radius of do. — No. of Stays to do. —  
 Dia. of stays. — Diameter of furnace Top 30" Bottom Length of furnace 5'-3" Thickness of furnace plates 7/16" Description of joint welded Thickness of furnace crown plates — Stayed by — Working pressure of shell by rules 86 lb  
 Working pressure of furnace by rules 91 lb Diameter of uptake — Thickness of uptake plates — Thickness of water tubes —

**SPARE GEAR.** State the articles supplied:— Propeller shaft, propeller, set of piston rings  
two top end bolts & nuts, 2 bottom end bolts & nuts, set of coupling bolts, feed  
& bridge valves, quantity of assorted iron etc.

The foregoing is a correct description,  
Hutton & Sons Ltd Manufacturer.

Dates of Survey while building { During progress of work in shops— 1901: Sep. 16. 17. 19. 21. 26. 28. Oct. 3. 16. 22. 26. Nov. 1. 4. 5. 12. 14. 19. 20. 22. 27. 30. Dec. 1.  
 { During erection on board vessel— 9. 12. 19. 23. 1902: Jan. 16. 17. 24. 30. Feb. 8. 11. 13. 17. 21. Mar. 10. Apr. 1. 7. 11. 15. 29. May. 5. 20. Jun. 5.  
 Total No. of visits 46 27. 29. 3. 10. 16 Is the approved plan of main boiler forwarded herewith Yes  
 " " " donkey " " Yes  
 " " " " " Yes

**General Remarks** (State quality of workmanship, opinions as to class, &c.) Also 2 Forging Reports

Material of screw shaft Iron Is the screw shaft fitted with a continuous liner the whole length of the stern tube No  
 Is the after end of the liner made water tight in the propeller boss Yes If the liner is in more than one length are the joints burned —  
 If the liner does not fit tightly at the part between the bearings in the stern tube, is the space charged with a plastic material insoluble in water and non-corrosive — If two liners are fitted, is the shaft lapped or protected between the liners Marlin about 4" up.

The engines & boilers of this vessel have been constructed under Special Survey & are of good materials & workmanship. They have been securely fitted on board & satisfactorily tried under steam.

This vessel is in my opinion eligible for notation L M C 7.02 in the Register Book.

It is submitted that  
 this vessel is eligible for  
 THE RECORD. + L M C 7.02

The amount of Entry Fee.. £ 2 : :  
 Special .. .. £ 32 . 3 : :  
 Donkey Boiler Fee .. .. £ : : :  
 Travelling Expenses (if any) £ : : :  
 When applied for, 28/7/02  
 When received, 1.8.02

H Gardner Smith  
 Engineer Surveyor to Lloyd's Register of British & Foreign Shipping.

Committee's Minute

Glasgow, 28 JUL 1902

Assigned

L. M. C. 7.02.  
 (Subject to classification of hull.)

MACHINERY CERTIFICATE  
 WRITTEN.

TUES. 5 AUG 1902

Lloyd's Register  
 Foundation