1 & 2 Dks., ~~Fcsle.~~, ~~Bridge~~, and ~~P.~~ Awng. ~~Deck~~

~~Iron~~ STEEL STEAMER.

No. 115453.

State if Report is also sent on the Machinery of the Vessel yes from Glasgow Received at London WED. 2 SEP 1908

Date of completion of Report 23rd August 1908. Port of GREENOCK.

Survey held at PORT GLASGOW Date, First Survey 26th March 08 Last Survey 21st August 1908

On the S.S. "NGAHERE" Rig SCHOONER.

ONE ~~Iron~~ ~~Steel~~ DECKED VESSEL.

CLASS + 100 A.1.

TONNAGE under Tonnage Deck	893.01
Do. of Poop Break	28.82
~~Do. of Raised Qr. Dk. or Bridge~~	
Do. of Bridge House	51.89
Do. of Forecastle	7.41
Do. of Houses on Deck	16.83
Do. of excess of Hatchways	53.72
Do. above Crown of Engine Room	38.52
Gross Tonnage	1090.20
Less Crew Space	77.49
Less above Crown of Engine Room	38.52
Tonnage for Fees	974.19
Less Engine Room	426.53
Less Navigation Spaces	30.13
Register Tonnage as cut on Beam	556.05

	Feet.
Half Breadth (moulded)	16.5
Depth from upper part of Keel to top of Main Deck Bms. (with the normal round up of beam)	17.34
Girth of Half Midship Frame (as per Rule)	31.10
1st Number	64.94
Length on deck from after part of stem to fore part of stern post	223.75
2nd Number	1453.32
Proportions—Breadths to Length	6.78
Depths to Length—Main Deck to top of Keel	12.9

RETAIN

Master JOSEPH MADDEN

Year of appointment (1) As master in service of owner of present vessel:—19 — (2) As master of this vessel 19 08

Built at PORT GLASGOW

When built 1908 Launched JULY 28TH 08

By whom built A. RODGER & Co

Owners THE BLACKBALL COAL Co LTD

Managers — (Where necessary to be entered in Reg. Book.)

Residence MANSION HOUSE CHAMBERS 20 BUCKLERSBURY LONDON E.C.

Port belonging to PORT GLASGOW

Destined Voyage AUCKLAND N.Z. If Surveyed while Building, Afloat, or in Dry Dock YES

	Feet.	Inches.		Feet.	Inches.		Feet.	Inches.	
LENGTH on Deck as per Rule	223	9	BREADTH—Moulded	33	0	DEPTH, ACTUAL—Top of Floors to top of Main Deck Beams	14	7	No. of Decks with Flat laid ONE; No. of Tiers of Beams ONE

Dimensions of Ship per Register, Length, 225 breadth, 33-15 depth, 15.7. Moulded Depth, 16 ft. 8 ins. Round of Beam, Actual 8 ins.

FRAMING.

	Inches in Ship.	Inches in Ship.	20ths in Ship.	Inches per Rule Or as	Inches per Rule as Approved	20ths per Rule ved.
FRAME, Angles, ~~Tee or~~ L Bars, for ⅜ length amidships	6	3	9	6	3	9
Do. for ½ at each end	6	3	8	6	3	8
Frames in way of Engine & Boiler space & Bunker increased 1/20 in thickness						
Do. in way of Double Bottoms at Solid Floors	3	3	6	3	3	6
" Peaks, ~~at intermdt. Bkts.~~	5	3	8	5	3	8
Spacing of Frames from centre to centre		23			23	
REVERSED FRAME, Angles ~~H.C.R.S.B.~~	3	3	6	3	3	6
DEEP FRAMING, depth of girder	.	6	.	.	6	.
FLOORS, depth and thickness of Floor Plate at mid-line ~~for ⅜ length~~ amidships under	19	x	11	19	x	10
" ~~in way of Engines and Boilers~~	BOILERS CELLULAR DOUBLE					
" thickness at the ends of vessel	BOTTOM EXCEPT					
" depth at ¾ the half breadth, as per Rule	UNDER BOILERS					
" height extended at the Bilges	.	4½	.	.	4½	.
FLOORS & BRACKETS, in ~~Cell Dble Bottoms~~ Increased 1/20 above Rules as shown	33	x	7	33	x	6
" " state if flanged (top & bottom)	NOT			FLANGED		
" " Spacing	.	23	.	.	23	.
CENTRE GIRDER, in Double Bottom, depth and thickness	33	x	8	33	.	8
" " Angles, Top SINGLE	5	5	9	5	5	9
" " " Bottom DBLE	3½	3½	9	3½	3½	9
SIDE GIRDERS, number on each side & thickness	ONE		7	ONE		7
" " state if flanged (top & bottom)	FLANGED TOP & BOTTOM					
" Angles ... VERTICAL	2½	2½	6	2½	2½	6
MARGIN PLATE, depth (exclusive of flange) and thickness increased 1/20 above Rule	22	x	8	22	x	7
" Angles to Outside Plating	3½	3½	7	3½	3½	7
" " Floors	3	3	6	3	3	6
" Height of Floors at the Bilges	3-1½			3-1½		
INNER BOTTOM PLATING, breadth and thickness of Middle Line Strake Increased 1/20 above Rule	33	x	9-8	33	x	8-7
" " thickness in Engine and Boiler space	.	.	9-8	.	.	7
" " " Remainder in Holds, no ceiling			9	Ceiling in hold 8		
BEAMS, Main ~~and Raised Quarter Deck~~, Single Angle, ~~Bulb Angle, Plate or Tee Bulb~~	6	3	8	6	3	8
" ~~Angles on Upper Edge~~ HALF BEAMS Angles	5½	3	8	5½	3	8
" Spacing	.	23	.	.	23	.
~~BEAMS, Lower Deck, Single Angle, Bulb Angle, Plate or Tee Bulb~~	.	.	.	.	.	.
" ~~Angles on Upper Edge~~	.	.	.	.	.	.
" ~~Spacing~~	.	.	.	.	.	.
~~BEAMS, Hold, Plate or Tee Bulb~~	.	.	.	.	.	.
" ~~Angles on Upper Edge~~	.	.	.	.	.	.
" ~~Spacing~~	.	.	.	.	.	.
BEAMS, Poop Deck, Angle, ~~Bulb Angle, Plate or Tee Bulb~~	5½	3	7	5½	3	7
" ~~Angles on Upper Edge~~	.	.	.	.	.	.
" Spacing	.	46	.	.	46	.
BEAMS, Bridge ~~or Pt. Awng.~~ Deck, Angle, Bulb Angle Plate, or Tee Bulb	6½	3	8	6½	3	8
" ~~Angles on Upper Edge~~ HALF BEAMS Angles	6	3	8	6	3	8
" Spacing		46			46	
BEAMS, Forecastle Deck, Angle, ~~Bulb Angle, Plate or Tee Bulb~~	5	3	6	5	3	6
" ~~Angles on Upper Edge~~	.	.	.	.	.	.
" Spacing	.	23	.	.	23	.
PILLARS, ~~In 'tween Decks,~~ Size and Spacing						
" " Hold	3½ to 3½	46 pc		3½ to 3½	46 pc	
" ~~Quarter 'tween Dks.~~ " "	and large brackets in way of Hatchways					
" " ~~in Hold~~ " "						
WEB FRAMES, ~~In Fore Body, No. and Spacing~~	.	.	.	.	.	.
" " ~~Brdth. & Thickness~~	.	.	.	.	.	.
" ~~No. of Side Stringers~~ " "	.	.	.	.	.	.
WEB FRAMES, In E. & B. Space, No. & Spacing	one face angle			5½ x 3½ x 9/20		
" ~~Inside Angle~~ Brdth. & Thickness	15 x 7/20			15 x 9/20		
WEB FRAMES, ~~In After Body~~, No. and Spacing	.	.	.	.	.	.
" " Brdth. & Thickness	.	.	.	.	.	.
" No. of Side Stringers " "	.	.	.	.	.	.
" Size of Angles or Tee Bars to Web Frames	.	.	.	.	.	.
BRACKET PLATES to Stringers between Web Frames, Depth and Thickness	.	.	.	.	.	.

FORGINGS AND CASTINGS.

	Inches in Ship.	Inches per Rule. Or as Approved.
KEEL, Bar or Side Plates depth and thickness	Flat plate Rule	
STEM, moulding and thickness RUBBING BAR 7½" x 1½"	7/16 x 2 3/8	7/16 x 2 3/8
STERN-POST for Rudder do. do.	7½ x 4 3/4	7½ x 4 3/4
" for Propeller	7½ x 4 3/4	7½ x 4 3/4
MAIN PIECE of Rudder, diameter at head	6	6
Single plate 19/20 do. at heel 3"	4½	4½

RUDDER, how constructed Single forged frame single plate

Can the Rudder be unshipped afloat? Yes

KEELSONS AND STRINGERS.

	Inches in Ship.	Inches in Ship.	20ths in Ship.	Inches per Rule Or as	Inches per Rule as Approved	20ths per Rule ved.
CENTRE LINE KEELSON, Vertical Plate above floors, Through Plate, or Intercostal Plate						
" Rider Plate						
" Bulb Plate to Intercostal Keelson						
" Horizontal Plates on Floors						
" Angles						
SIDE KEELSON, Angles						
" Bulb or Plate above floors for lng.						
" Intercostal Plate for length						
" Attached to outside plating with Angle						
BILGE KEELSON, Angles						
" Bulb or Plate above floors for lng.						
" Intercostal Plate for length						
" Attached to outside plating with Angle						
BILGE STRINGER Angles						
" Bulb Plate for length						
" Intercostal Plate for length						
" Attached to outside plating with Angle						
SIDE STRINGERS Angles on face	5½	3½	9-8	5½	3½	9-8
" Bulb or Intercostal Plate for Whole lng.		12½			12½	
" Attached to outside plating with Angle	3	3	7-6	3	3	7-6
Intercostal Rider in Boiler space			9			9
Main ~~and Raised Quarter~~ Deck Stringer Plate, breadth and thickness 1/2 space. Ends	8½		10	8½		10
" Angle on ditto	4 x 4 x		8	4 x 4 x		8
" Tie Plates, outside Hatchways	.		.	.		.
" Diagonal Tie Plates on Bms., No. of Pairs	.		.	.		.
" Main Dk* ~~Iron or~~ Steel for Whole lng.	.		6-8	.		6-8
" R. Q. Dk* Iron or Steel for lng.	.		.	.		.
" Wood Deck, Material & thickness	.		.	.		.
Lower Deck Stringer Plate, breadth and thickness	.		.	.		.
" Angles on ditto, No.	.		.	.		.
" Tie Plates, outside Hatchways	.		.	.		.
" Deck* Material and thickness	.		.	.		.
Hold Stringer Plate	.		.	.		.
" Angles on ditto, No.	.		.	.		.
Poop Deck Stringer Plate, breadth & thickness	22	6		22	6	
" Angle on ditto	3½ x 3½ x	7		3½ x 3½ x	7	
" ~~Tie Plates~~ STEEL DK PLATING	.	4		.	4	
" Deck, Material and thickness SHEATHING	3" pine			3" pine		
Bridge ~~or Pt. Awning~~ Deck Stringer Plate, breadth and thickness	8	8		8	8	
" Angle on ditto	3½ x 3½ x	8		3½ x 3½ x	8	
" Tie Plates STEEL DK PLATING	.	5		.	5	
" Deck, Material and thickness SHEATHING	3" pine			3" pine		
Forecastle Deck Stringer Plate, brdth & thckns	22	6		22	6	
" Angle on ditto	3½ x 3½ x	7		3½ x 3½ x	7	
" ~~Tie Plates~~	.	.		.	.	
" Deck, Material and thickness STEEL DK	.	5		.	5	

Deep frames and cellular double bottoms under Boilers

* If Iron or Steel Deck, state if whole or part, and if wood deck is laid thereon.

BULKHEADS.

	Number. In Vessel.	Number. Per Rule.	Thickness. 16ths or 20ths.	STIFFENERS. Horizontal. Size. Inches.	Horizontal. Spacing Inches.	Vertical. Size. Inches.	Vertical. Spacing Inches.	Single or Double Frames.	Height up.
W.T. BULKHEADS	4	4	6/20	none		6x3x7/16 BA	28	Single	to B.D.
								4½x4½x9/16	
PARTITION "	1	—	6/20	do		4x3x7/16	30	Single	.
LONGITUDINAL "	none								

Are the outside Plates doubled two spaces of Frames in length? Yes

Are the ~~Sluice Valves and~~ Watertight Doors in efficient working order? Yes

W768 — 0095½

© 2011 Lloyd's Register Foundation

Rpt. 1A. 5c.6,6.

PLATING.

RIVETING.

STRAKES.	AS IN SHIP. Amidship. Breadth.	Amidship. Thickness.	Forward. Thickness.	Aft. Thickness.	PER RULE OR AS APPROVED. Amidship. Breadth.	Amidship. Thickness.	EDGES. Ordinary or Joggled? Joggled. Single or Double.	Breadth of Lap.	Rivets. Diam.	Rivets. Spacing cr. to cr.	Butts. Double or Treble and for what Length.	Rivets. Diam.	Rivets. Spacing cr. to cr.	Straps. Breadth.	Straps. Thickness.	If Lapped. Breadth.	If Lapped. For what Length.
	Inches.	10ths or 20ths	10ths or 20ths	10ths or 20ths	Inches.	10ths or 20ths		Inches.	Inches.	Inches.		Inches.	Inches.	Inches.	10ths or 20ths	Inches.	Feet.
Flat Plate Keel (If Bar Keel, state Riveting)	34	14	11	11	34	14	Double	5¼	7/8	3⅜	3R Rm	1	3½	19	16	–	–
Garboard or A Strake	72	10	9	9	72	10	"	"	"	"	4R 3½L	7/8	"	–	–	12	Whole
State actual thickness in way of Double Bottom. B "	72	9	9	10	72	9	"	"	"	"	4R 3¼L	"	"	–	–	"	"
C "	66	11	10	10	66	10	"	"	"	"	4R ½L	"	"	–	–	"	"
D "	72	10	9	10	72	9	"	"	"	"	4R ½L	"	"	–	–	"	"
E "	72	11	9	9	72	10	"	"	"	"	4R ½L	"	"	–	–	"	"
(Sheer) F "	48	14	10	10	48	13	"	"	"	"	3R ½L	1	"	–	–	10½	"
G "																	
H "	The bottom is strengthened forward of the 3/5 length in accordance																
J "	with Section 12 a. The runner plating is 5/20 increased 2/20																
K "	under hatchways & stiffeners 3×3½×6/20. The bore for the																
L "	coaling screw shaft is 1/20 thicker than amidships																
M "	An American Elm belting is fitted as runners all fore & aft of 8⅝×8"																
N "	angles 5½×4×10/20 with face plate. 5"×7/8".																
O "	IT MAY BE NOTED THAT THE THICKNESS OF C.D.E & F STRAKES IS INCREASED 1/20 ABOVE THE RULES ALL FOR FAST.																
P "	ALSO THE THICKNESS OF FLOORS TANK BRACKETS, MARGIN PLATES & TANK TOP INCREASED 1/20 AND THE SIDE FRAMES																
Double Bottom or Flat Plate Keel	IN ENGINE & BOILER SPACE AND CROSS BUNKER INCREASED 1/20 and as is usual this increase																
Length and thickness of Bilges	may be noted upon the certificate of classification																
The 2 Sheerstrakes	HAS BEEN INCREASED IN THICKNESS 3/20 OUTSIDE BRIDGE FOR ½ LENGTH & DOUBLED AT ENDS OF BRIDGE for 20 ft																
The Strake below Sheerstrake	"HAS BEEN INCREASED 1/20 FOR HALF LENGTH OUTSIDE BRIDGE.																
Poop Sides	–	–	–	6	60	6	Single	3	3/4	3⅜	Double	3/4	2⅝	–	–	5	Whole
~~Raised Quarter Dk. Sides~~																	
Bridge Sides	–	8	–	–	–	8	Do	3	3/4	3⅜	Treble	3/4	2⅝	–	–	7½	Do
Forecastle Sides	–	–	6	–	–	6	Do	3	3/4	3⅜	Double	3/4	2⅝	–	–	5	Do
Lengths of Plating	ELEVEN FRAME SPACES.																

Manufacturer's name or trade mark of the Iron or Steel (state process of manufacture of Steel) used for Frames, Floors, Beams, Keelsons, Tie and Stringer Plates, outside Plating, &c.? SIEMENS MARTINS PROCESS.
STEEL, DALZELL, GILCHRIST & LANARKSHIRE, HALLSIDE, CALDERBANK.
IRON, COATS, WAVERLEY.
Has the Steel been tested as required by the Rules YES.

Main Stringer Plate Butts, treble riveted for HALF length amidship, Straps, ~~single, double or~~ overlapped for ~~half~~ length ~~amidship~~
Butts of Bilge & Side Stringers, and Tie Plates, treble ~~or double~~ riveted? Yes
Inner Bottom Plating, riveting of Edges Single Butts R 2 Rm 2 Spaces
Centre Girder Butts, Treble riveted. **Keelson Butts,** Treble riveted.
Frames, riveted through Plates with 7/8 in. Rivets, about 6⅛ apart.
Rivets, state whether of Iron or Steel Steel

FRAMES extend in one length from CENTRE LINE TO MARGIN PLATE THENCE TO GUNWALE state if ~~ordinary or~~ joggled Yes
REVERSED FRAMES on floors and frames extend from CENTRE LINE TO MARGIN. DOUBLE IN ENGINE SPACE state if ~~ordinary or~~ joggled Yes
Bulb angle Framing SINGLE BOILER SPACE 5"×3½×9/20

MASTS, SPARS, &c.

		Material.	Total length.	Diameter and Thickness. At Partners.	Heel.	Hounds.	Head.	No. of Plates in round.	Angles. Number.	Angles. Size.	Riveting. Seams.	Riveting. Butts.
Lower Masts	Fore	STEEL	93'-6"	19×2½0	17×6/20	15½×6/20	8×5/20	Two	Two	3½×3×2/20	SINGLE	TREBLE
	Main	Do	88-6	Do	Do	Do	Do	Do	Do	Do	Do	Do
	~~Mizen~~											
~~Bowsprit~~												

Topmasts, Yards and Remainder of **Spars** pitch pine
Rigging, Material and Size, **Shrouds** galvanised steel wire 3½ . **Stays** galvanised plate wire 4"
Sails One complete Suit of fore rafe schooner Sails and the following spare sails none

Equipment No. 15623 Letter N . Tonnage U.Dk. or Plating No. for Trawlers none

ANCHORS.

a certificate of a test examined

Number of Certificate.	Anchors.	Weight, Ex Stock Cwts.	qrs.	lbs.	Weight of Stock. Cwts.	qrs.	lbs.	Test, per Certificate. Tons.	Cwts.	qrs.	lbs.	Weight Required by Table 22. Cwts.	qrs.	lbs.	Description of Anchor.	Makers.	Where and when tested and Superintendent.
A 10999	1st Bower	25	3	0	.	.	.	25	8	0	14	25	2	0	STOCKLESS	W. L. Byers	Pum 3/6/08 T. J. Reid
A 11000	2nd "	25	2	21	.	.	.	25	8	0	14	25	2	0	Do	Do	Do Do Do
K 10984	3rd "	22	1	14	.	.	.	22	13	0	14	22	0	0	Do	Do	Do 28/5/08 Do
	Collective weight	73	3	7								73	0	0			
60952	Stream	6	2	15	1	3	2	9	0	0	0	6	2	0	ORDINARY	T. P. Jones & Co	Neth 4/6/08 T. J. Reid
60951	Kedge	3	2	5	0	3	22	6	0	3	21	3	2	0	Do	Do	Do Do Do

If Patent state Name of Patentee. If Stockless state Mechanism.

CHAIN CABLES.

Number of Certificate.	Length and size supplied. Length. Fathoms.	Diam. Ins.	Test per Certificate. Statutory. Tons.	Breaking. Tons.	Weight of Chain Cable. Supplied. Cwts. qrs. lbs.	Per Table 22. Cwts. qrs. lbs.	Length & Size per Table 22. Length. Fathoms.	Diam. Ins.	Description.	Makers of Cables.	Where and when tested and Superintendent.
42451	105	1½	40½	58 70/90	12-1-2-0	242-0-5	210	1½	Stud	T. P. Jones & Co	Neth 23/5/08 T. J. Reid
42461	105	1½	40½	58 70/90	–	–	Do	"	"	Do	" 27/5/08 "
42459	spare shackle for 1st chain				15-16-0-0	nil 106					" 22/5/08 "
Iron Stream Chain or Steel Wire	75	3½ in dia					75	3½	(Steel wire)	Rhiwgoch & Co Ltd.	

HAWSERS AND WARPS.

Material.	Length and Size supplied. Length. Fathoms.	Cir. Ins.	Breaking Test of Steel Wire Towline. Tons.	Length and Size per Table 22. Length. Fathoms.	Cir. Ins.
Towline	90	3¼	22	90	3½ wire
Hawsers & Warps	90	2¼	9½	90	6
" "	110	2½	12½	90	8
" "	90	5 manilla			
	120	8½			

Boats 2 lifeboats and 1 Dingy
Pumps, Number 2½ Downton in E.R. & hand pump in after hold Diameter of Barrel 4½ State whether they are in efficient working order Yes
Windlass is Clarke Chapmans Patent Steam Capstan none fitted. 4 steam winches
Engine Room Skylights.—How constructed? Steel plates & steel bars covered (hinged) with bulls eyes
What arrangements for deadlights in bad weather? Steel bars covered (hinged) with bulls eyes
Coal Bunker Openings.—How constructed? Steel How are lids secured? Cleats & battens Height above deck? 12"
Number of **Scuppers,** and number and dimensions of **Freeing Ports,** &c. 4 each side and 6 ports each side 30"×22"
Ceiling in Holds, thickness and material none fitted **Cargo Battens,** thickness and material none fitted
Cargo Hatchways.—How formed? Steel plates and angles **Hatches.**—If strong and efficient? Yes 3" P.D.
State size **No. 1 Hatch** (Forward) 23'×18'8/16×4½" **No. 2 Hatch** 23'-0"×18"×42" **No. 3 Hatch** 23'×18"×42" **No. 4 Hatch** 23'×18"×42"
Number of **Web Plates,** ~~Shifting Beams and Fore and Afters~~ to each Hatch as approved four shifting beams to each hatchway one for rafters.
No. of Breasthooks 5 **No. of Crutches** Deep floors
Bulwarks, height above deck and description 5/20 steel plates 5'4" above Dk. Main Rail and Stays, material and size Rail & B.A. 6"×3×7/20 Stays & Bulwark plate 6×6/20

The above is a correct description.
Builder's Signature (here only). A. Rodger & Co
Surveyor's Signature Edward W. Tierney
Surveyor to Lloyd's Register of British and Foreign Shipping.

Rpt. 1A.

Correspondence.—State dates and initials of letters respecting this case (*Reference should be made to any correspondence connected with the case*) M 19/1/08 20/2/08 22/2/08 M 14/3/08 E 1/4/08

Workmanship. Are the butts of plating planed or otherwise fitted? planed where practicable
Is the riveted work properly closed? Yes
Are the liners between the frames and plates solid single pieces? Frames jogged Do the holes for riveting plate to frames, butt straps, or plate to plate, &c., conform well to each other? Yes Are the rivet holes well and sufficiently countersunk in the plate and punched from the faying surfaces? Yes Do any rivets break into or through the seams or butts of the plating? No
Are the butts of Plating, Stringers, &c., properly shifted and strapped? Yes
Have all the upper and weather decks been tested as required by the Rules (Sec. 23, par 24)? Yes State results of tests Satisfactory
Have all the gutterways been tested as required by the Rules (Sec. 23, par. 25)? Yes State results of tests None

General Remarks (State quality of workmanship, &c.) This steel screw steamer has been built in accordance with the approved plans and the Society's Rules & Secretary's letters. The quality of the materials and the workmanship is good. The keel was sighted and found to be straight & the moulded depth to be checked before being launched.

The Surveyor should state the Number of Report and Name of any Sister Vessel. (none)

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 20 ft., R.Q.D. Break nil, Bridge Dk. 58 ft., F'castle 21'6 ft. (in feet and tenths) where the Poop is on top of the R.Q.D., or when the Poop or R.Q.D. is joined to the B.D., this should be distinctly stated The poop is a Sunk or Half poop & is not connected to Bridge
No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (*the information is to be given as it should appear in the Register Book*) 1 DK (Steel) and Deep Framing
Official No. ; Signal Letters State if Machinery is fitted aft
How are the surfaces preserved from oxidation? Inside paint & Cement Outside paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors C.D.B.

Where fitted.	*Length. Feet.	Water Capacity. Tons.	Where fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,	70-11"	97	Fore peak tank,	–	28
Double bottom, under Engines ~~and Boilers~~ (Fresh water)	15-4"	31	After peak tank,	–	32
~~Double bottom if under Engines only,~~			~~Deep tank, aft~~		
~~Double bottom, if under Boilers only,~~ ORDINARY FLOORS UNDER BOILERS.			~~Deep tank, forward~~		
Double bottom, forward,	84-4	135	~~Other tanks, if fitted,~~		
	Total capacity	263	(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks. State whether the above have been tested as required by the Rules Yes

Order for Special Survey No. 2501
Date 11th March 1908
No. 407 in builder's yard.

Dates of Surveys held while building: 1908. Mar 26. 30. April 1. 3. 8. 10. 15. 17. 20 23. 28. 29. May 4. 7. 11. 14. 18. 20. 22. 26. 27. 30 June 4. 8. 12. 19. 22. 24. 29. July 15. 16. 17. 21. 27. 28. August 17. 21.

Total No. of Visits 37.

The amount of Entry Fee £ 3 : : Fees applied for, 24/9/1908
Special £ 48 : 14 : Received by me, 25/9/1908 D.Mk.
Travelling Expenses, if any £ : : Certificate to be sent to Freeman
State whether the Vessel has been built under Special Survey Yes
I am of opinion this Vessel should be Classed + 100 A.1.
~~Not~~ without Freeboard, as condition of Class Yes

Edward W. Tierney
Surveyor to Lloyd's Register of British and Foreign Shipping

Committee's Minute GLASGOW 1 SEP. 1908
Character assigned + 100 A1 (Steel) 8.08. Lloyd's a+cp. + LMC 8.08. (2 Cargo battens only) See Gls. Vc. 9/9/08 L.B.C.

The Surveyors are requested not to write on or below the Committee's Minute.

© 2021 Lloyd's Register Foundation

W708-0095 3/2