

RS AND WARPS.

Fathoms.	Size.	Breaking Test of Steel Wire Towline.	Fathoms Size
90	9		90
60	3½		90
60	6"		90
90	5"		
140	2½		

lans.  
stet wire  
it any mast.  
ail

ntan pump  
th. also connectio  
g on board?  
tens to steam pu

ck, framing 10" the

10'0" x 16'0"

6 Dec. 5. 17. 30. 1919 - Jan

10. 1910. Feb. 16. May 5. Jan 2

5. Oct. 11. Nov 4. 16.

ere falvanized  
water) Built end.

8 dia. clenched an

st. clenched over re

ia - 11 - 11 - 11

are in each.

it in accordance

way of the mast.

Las burn

in general.

manship 2.

26. Aug. 18<sup>th</sup>

at no auxiliary

in fitted.

in all

's Register of Shipping.

Copy.

TUE. DEC. 14 1910

GLASGOW.

15th March, 1919.

PETER McGRIGOR

Messrs. Cochran & Co. (Annan) Ltd., Annan, examine the donkey boiler No. 7704 made by them to the order of the Leclaire Shipbuilding Co. Ltd., of Sorel, Que.

The scantling of the boiler were found to be in accordance with the Rules of Lloyd's Register for a working pressure of 100 lbs. per square inch. The Steel Material used in the construction of the boiler was tested by the Society's Surveyors in accordance with the Rules, and the workmanship so far as seen was good.

The boiler was tested by hydraulic pressure to 200 lbs. per square inch in the presence of the undersigned Surveyor, and was found sound and tight at that pressure.


Working pressure not to exceed One Hundred Pounds per square inch.

Peter W. Chegor

Marks on Boiler No. 7704

No. 14640  
Lloyd's Test  
200 lbs.  
P.W.C. 14/3/19.

Surveyor to Lloyd's Register.



© 2020

Lloyd's Register  
Foundation

W710-0195