Deck as per Rule | 480 | 8 | Moulded | 82 | 8 | Do. | do. | Upper Deck Beams | 32 | 11½ | No. of Tie

Dimensions of Ship per Register. | 41·4 | Awn or Shelter Dk | Moulded depth ft. 44 ins. 3 | To Awning or Shelter Dk | Round

Im.8.21.

F.E.

Received by Chief Ship Surveyor ..... *Received from Chief Ship Surveyor* .....

VESSEL'S NAME Steel S.S. "Port Brisbane" Rpt. Bel. No. 9014

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—*Extract from Sub-Committee's Report*, 24/5/92.)

Transverse No. 98·25 Depth "d" 20·92

Framing: Table No. 3 Description Channels and reverse frames.

Longitudinal No. 47160

Proportions $\frac{\text{Length}}{\text{Depth}}$ = 10·85

Shelter Deck Sheerstrake as approved.

This vessel appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed ✠ 100. A.1. (Steel) "Shelter Dk. with freeboard," as recommended. The Summer freeboard of 6'- 5" from centre of disc to top of statutory deck line at upper deck, now marked on the vessel's sides, to be inserted in the classification certificate, and recorded in the Register Book, and further, the remaining freeboards, as shown on the accompanying verification form to be inserted in the certificate of classification.

2 Dks (Stl) & Shelter Dk (Stl-ws).
Cell DB 414' 147 8t, APT 80t,
FK, Collision BH to Shelter Dk. 78H to upper Dk. Cem, Lloyds A.&C.P.
F on Shelter Dk 56'.

A.W.J. 11/12/23.

W73-0078

© 2019 Lloyd's Register Foundation

" Spacing ..... 54 9 48 54 9 48 " Deck. Material and thickness Sheathing 5×3 P. Pine