

Spar, or ~~Awning~~ Dk.

IRON OR STEEL STEAMER.

No.

13100.

THUR. 25 OCT 1806

State of Report is also sent on the Machinery of the Vessel.

Port of WEST HARTLEPOOL Date of completion of Report 24 October 1906Received at London Office 24 October 1906Survey held at West Hartlepool Date, First Survey 19 MayLast Survey 19 October 1906

On the

Screw Steamer"TANCISTAN"

Rig

Schooner

TONNAGE under

Tonnage Deck...  
Do. between Tonnage Dk.  
and 3rd, 4th, Spar or  
Awning Dk.Total under Upper Dk. 3484.10

Do. of Poop

Do. of Bridge House

Do. of Forecasts

Do. of Houses on Deck

Do. of excess of Hatchways

Do. above Crown of

Line Room ...

Tonnage

Screw Space

Above Crown of

Line Room ...

SE FOR FEES...

Engine Room

Navigation Spaces

Total Tonnage

on Beam...

SPAR, AWNING OR PART AWNING-DECKED VESSEL,

on a Vessel having a continuous Shade Deck

CLASS

FEET.

Half Breadth (moulded) ...

Depth from upper part of keel to top of Main Deck Beams

Girth of Half Midship Frame (as per Rule)

1st Number

Length

2nd Number

Proportions—Breadths to Length

Depths to Length—Main Deck to top of Keel

Destined Voyage

Master L. S. Sadler

Year of Appointment

Built at West HartlepoolWhen built 1906 Launched 19th Sept 1906By whom built W. Gray & Co LtdOwners Anglo Algerian Steamship Co 1896 LtdManagers J. B. Strick & Co Ltd

Residence

Port belonging to

LondonSwansea

\* Surveyed while Building, Afloat, or in Dry Dock

| DEPTH on Deck | Feet. | Inches. | BREADTH | Feet. | Inches. | DEPTH, top of Floors to Spar or Awning Dk. Beams | Feet. | Inches. | Power of Engines | Horse. | No. of Decks with flat laid |
|---------------|-------|---------|---------|-------|---------|--|-------|---------|------------------|--------|-----------------------------|
| per Rule      | 348   | 2       | Moulded | 49    | 0 1/2   | Do. do. Main Deck Beams                          | 16    | 4       |                  |        | two                         |

Dimensions of Ship per Register, Length 350 breadth 49.2 depth 24.3 Spar or Awning Dk. Moulded depth, ft. 18 ins. 10 To Main Dk. Round up of Beam, Main Dk. 12 ins.

| FRAMING.   |                 |                 |                                | FORGINGS AND CASTINGS. |                 |                                 |          |
|--|-----------------|-----------------|--------------------------------|------------------------|-----------------|---------------------------------|----------|
|  | Inches in Ship. | Inches in Ship. | 20ths per Rule Or as Approved. |                        | Inches in Ship. | Inches per Rule Or as Approved. |          |
| ME, Angles, or L or Bars, for length amidships                         | 9               | 3 1/2           | 11                             | 9                      | 3 1/2           | 11                              |          |
| o. for 1/2 at each end   |                 |                 | 10                             |                        |                 | 10                              |          |
| o. in way of Double Bottoms at Solid Floors                            | 3 1/2           | 3 1/2           | 9                              | 8                      | 3 1/2           | 9                               | 8        |
| at intermdt. Bkts.   |                 |                 |                                |                        |                 |                                 |          |
| ance of Frames from moulding edge to                                   | 25              |                 | 25                             |                        |                 |                                 |          |
| moulding edge, all fore and aft  | 3 1/2           | 3 1/2           | 8                              | 3 1/2                  | 3 1/2           | 8                               |          |
| VERSED FRAME, Angles   | 9               |                 | 9                              |                        |                 |                                 |          |
| EP FRAMING, depth of girder  |                 |                 |                                |                        |                 |                                 |          |
| DOORS, depth and thickness of Floor Plate                              | 8               | 8               | 8                              | 8                      | 8               | 8                               |          |
| at mid line for 1/2 length amidships                                   |                 |                 |                                |                        |                 |                                 |          |
| in way of Engines and Boilers  | 6               | 20              | 8                              | 16                     | 8               | 16                              |          |
| thickness at the ends of vessel  |                 |                 |                                |                        |                 |                                 |          |
| depth at 1/2 the half b'dth. as per Rule                               | 6 1/2           |                 | 6 1/2                          |                        |                 |                                 |          |
| height extended at the Bilges  |                 |                 |                                |                        |                 |                                 |          |
| DOORS & BRACKETS, in Cell Dble Bottoms                                 |                 |                 |                                |                        |                 |                                 |          |
| Distance apart   | 25              |                 | 25                             |                        |                 |                                 |          |
| NTR E GIRDER, in Double bottom, depth and thickness                    | 4 1/2           |                 | 12                             | 8                      | 4 1/2           | 12                              | 8        |
| Angles, Top  | 4               | 4               | 9                              | 4                      | 4               | 9                               |          |
| Bottom   | 4               | 4               | 12                             | 11                     | 4               | 12                              | 11       |
| DE GIRDERS, number and thickness                                       | 2               |                 | 8                              | 2                      |                 | 8                               |          |
| Angles   | 3 1/2           | 3 1/2           | 8                              | 3 1/2                  | 3 1/2           | 8                               |          |
| REGIN PLATE, depth (exclusive of flange) and thickness                 | 33              |                 | 9                              | 33                     |                 | 9                               |          |
| Angles   | 4               | 4               | 9                              | 4                      | 4               | 9                               |          |
| NER BOTTOM PLATING, breadth and thickness of Middle Line Strake        | 58              |                 | 10                             | 8                      | 42              | 10                              | 8        |
| thickness in Engine and Boiler space                                   | 10              |                 | 7                              | 8                      | 10              | 7                               | 8        |
| Remainder in Holds   |                 |                 |                                |                        |                 |                                 |          |
| EAMS, Spar or Awning Deck, Single Angle, Bulb Angle, Plate or Tee Bulb | 9               | 3 1/2           | 11                             | 9                      | 3 1/2           | 11                              |          |
| Angles on upper edge   | 9 1/2           | 3 1/2           | 13                             | 9 1/2                  | 3 1/2           | 13                              |          |
| Average space  | 25              |                 | 25                             |                        |                 |                                 |          |
| EAMS, Main Deck, Single Angle, Bulb Angle, Plate or Tee Bulb           | 10              | 3 1/2           | 12                             | 10                     | 3 1/2           | 12                              |          |
| Angles on upper edge   |                 |                 |                                |                        |                 |                                 |          |
| Average space  | 25              |                 | 25                             |                        |                 |                                 |          |
| EAMS, Lower Deck, Single Angle, Bulb Angle, Plate or Tee Bulb          |                 |                 |                                |                        |                 |                                 |          |
| Angles on upper edge   |                 |                 |                                |                        |                 |                                 |          |
| Average space  |                 |                 |                                |                        |                 |                                 |          |
| EAMS, Hold, or Orlop, Plate or Tee Bulb                                |                 |                 |                                |                        |                 |                                 |          |
| Angles on upper edge   |                 |                 |                                |                        |                 |                                 |          |
| Average space  |                 |                 |                                |                        |                 |                                 |          |
| EAMS, Poop Deck, Angle, Bulb Angle, Plate or Tee Bulb                  | 6 1/2           | 3               | 9                              | 6 1/2                  | 3               | 9                               |          |
| Angles on upper edge   |                 |                 |                                |                        |                 |                                 |          |
| Average space  | 25              |                 | 25                             |                        |                 |                                 |          |
| EAMS, Bridge Deck, Angle, Bulb Angle, Plate or Tee Bulb                | 7 1/2           | 3               | 10                             | 7 1/2                  | 3               | 10                              |          |
| Angles on upper edge   |                 |                 |                                |                        |                 |                                 |          |
| Average space  | 25              |                 | 25                             |                        |                 |                                 |          |
| EAMS, Forecastle Deck, Angle, Bulb Angle, Plate or Tee Bulb            | 10              |                 | 10                             |                        |                 |                                 |          |
| Angles on upper edge   | 3 1/2           | 3 1/2           | 7                              | 3 1/2                  | 3 1/2           | 7                               |          |
| Average space  | 50              |                 | 50                             |                        |                 |                                 |          |
| PILAKS, In tween Deck, size and spacing                                | 3               |                 | 50                             | 5                      |                 | 50                              |          |
| Hold   | 5               |                 | 50                             | 5                      |                 | 50                              |          |
| Quarter, tween Dks.,   |                 |                 |                                |                        |                 |                                 |          |
| in Hold  |                 |                 |                                |                        |                 |                                 |          |
| WEB FRAMES, In Fore Body, No. and spacing breadth & thickness          |                 |                 |                                |                        |                 |                                 |          |
| No. of Side Stringers  |                 |                 |                                |                        |                 |                                 |          |
| WEB FRAMES, In E. & B. Space, No. & spacing breadth & thickness        |                 |                 |                                |                        |                 |                                 |          |
| WEB FRAMES, In After Body, No. and spacing breadth & thickness         |                 |                 |                                |                        |                 |                                 |          |
| No. of Side Stringers  |                 |                 |                                |                        |                 |                                 |          |
| Sign of Angles or Tee Bars to Web Frames                               |                 |                 |                                |                        |                 |                                 |          |
| BRACKET PLATES to Stringers between Web Frames, depth and thickness    |                 |                 |                                |                        |                 |                                 |          |
| BULKHEADS.   |                 |                 |                                | STIFFENERS.            |                 |                                 |          |
|  | In Vessel.      | Per Rule.       | Thickness.                     |                        | Horizontal.     | Vertical.                       | Spacing. |
| W. T. BULKHEADS  | 6               | 6               | 6                              | 7                      | 7 1/2           | 3                               | 10       |
| PARTITION  | 1               | 1               | 5                              | 5                      | 5 1/2           | 3                               | 9        |
| LONGITUDINAL   |                 |                 |                                |                        |                 |                                 |          |
| Are the outside Plates doubled two spaces of Frames in length?         |                 |                 |                                |                        |                 |                                 |          |



