

and
1 or 2 Dks., R. Q. Dk.,
and Pt. Awng. Dk.

IRON OR STEEL STEAMER.

No. 18482

THUR. NOV 8 1906

State if Report is also sent on the Machinery of the Vessel *Yes*

Received at London Office,

Date of completion of Report *6th November 1906*
Date, First Survey *June 15th*

Port of Hull

Last Survey

Oct. 29th 1906.

Rig Ketch.

Survey held at *Belley*

On the *Steam Trawler "LORD NUNBURNHOLME"*

TONNAGE under Tonnage Deck... 238.95

Do. of Poop 14.78

Do. of Raised Qr. 6.13

Do. of Break... 11.07

Do. of Bridge House 240.93

Do. of Forecastle 24.91

Do. of Houses on Deck 11.07

Do. of excess of Hatchways 234.95

Do. above Crown of Engine Room 138.46

Gross Tonnage 9.43

Less Crew Space 11.07

Less above Crown of Engine Room 234.95

TONNAGE FOR FEES.. 138.46

Less Engine Room 9.43

Less Navigation Spaces 11.07

+ Above Crown of Engine Room 234.95

Register Tonnage 98.13

as cut on Beam ..

ONE OR TWO DECKED VESSEL.

CLASS 100A1 Steam Trawler

Half Breadth (moulded) 11.08

Depth from upper part of Keel to top of Main Deck Bms. 13.20

Girth of Half Midship Frame (as per Rule) 19.82

1st Number 44-10

Length on deck from after part of stem to fore part of stern post 128.93

2nd Number 5681

Proportions—Breadths to Length 5.8

Depths to Length—Main Deck to top of Keel 9.7

Destined Voyage *Fishing*

Master

Year of appointment

Built at *Belley*

When built *1906* Launched *4th September*

By whom built *Cochran & Sons*

Owners *The Yorkshire Steam Fishing Co., Ltd.*

Managers

(Where necessary to be entered in Reg. Book.)

Residence *Hull*

Port belonging to *Hull*

and *Yes*

If Surveyed while Building, Afloat, or in Dry Dock

LENGTH on Deck as per Rule.....		Feet. 128	Inches. 10	BREADTH— Moulded.....		Feet. 22	Inches. 2	DEPTH, ACTUAL— Top of Floors to top of Main Deck Beams		Feet. 12	Inches. 0	No. of Decks with Flat laid	One	No. of Tiers of Beams	One
Dimensions of Ship per Register. Length, 130-0 breadth, 22-3 depth, 11-92 . Moulded Depth, 12 ft. 9 ins. Round of Beam, Actual 7 ins.															

Dimensions of Ship per Register, Length, 130-0 breadth, 22-3 depth, 11-92. Moulded Depth, 12 ft. 9 ins. Round of Beam, Actual 7 ins.

FRAMING.		Inches in Ship.	Inches in Ship.	16ths in Ship.	Inches per Rule Or as	16ths per Rule	FORGINGS AND CASTINGS.		Inches in Ship.	Inches per Rule. Or as Approved.
FRAME, Angles, T.E. or L. Bars, for 1/2 length amidships		4	3	7	4	3	7	KEEL, Bar or Side Plates depth and thickness	8 x 2	8 x 2
Do. for 1/2 at each end								STEM, moulding and thickness.	8 x 2	8 x 2
Do. in way of Double Bottoms at Solid Floors..								STERN-POST for Rudder do. do.	6 x 3	6 x 3
" " at intermdt. Bkts.								" for Propeller	4 1/2	4 1/2
Spacing of Frames from centre to centre		20				20		MAIN PIECE of Rudder, diameter at head.	3 1/2 x 3	3 x 2 1/2
" do. at heel								do.		
REVERSED FRAME, Angles (on top of floors)		2 1/2	2 1/2	4	2 1/2	2 1/2	4	RUDDER, how constructed	Forged iron frame, plated.	
DEEP FRAMING, depth of girder		4				4		Can the Rudder be unshipped afloat?	Yes	
FLOORS, depth and thickness of Floor Plate at mid-line for 1/2 length amidships		16		6	16		6	KEELSONS AND STRINGERS.		
" in way of Engines and Boilers				7			7	CENTRE LINE KEELSON, Vertical Plate above floors, Through Plate, or Intercoastal Plate	7 1/2	7
" thickness at the ends of vessel				6			6	" Rider Plate		
" depth at 1/2 the half breadth, as per Rule		Straight across						" Bulb Plate to Intercoastal Keelson		
" height extended at the Bilges		plan						" Horizontal Plates on Floors		
FLOORS & BRACKETS, in Cell Dble Bottoms								" Angles	5	3
" " state if flanged (top & bottom)								" SIDE KEELSON, Angles		
" " Spacing								" Bulb or Plate above floors for lng.		
CENTRE GIRDER, in Double Bottom, depth and thickness								" Intercoastal Plate for length		
" " Angles, Top								" Attached to outside plating with Angle		
" " Bottom								BILGE KEELSON, Angles	3	3
SIDE GIRDERS, number on each side & thickness								" Bulb or Plate above floors for lng.		
" " state if flanged (top & bottom)								" Intercoastal Plate for length		
" " Angles								" Attached to outside plating with Angle		
MARGIN PLATE, depth (exclusive of flange) and thickness								BILGE STRINGER Angles		
" " Angles to Outside Plating								" Bulb Plate for length		
" " Floors								" Intercoastal Plate for length		
" " Height of Floors at the Bilges								" Attached to outside plating with Angle		
INNER BOTTOM PLATING, breadth and thickness of Middle Line Strake								SIDE STRINGER Angles	3	3
" " thickness in Engine and Boiler space								" Bulb or Intercoastal Plate for lng.		
" " Remainder in Holds								" Attached to outside plating with Angle		
BEAMS, Main and Raised Quarter Deck, Single Angle, Bulb Angle, Plate or Tee Bulb		5	3	8	5	3	8	Main and Raised Quarter Deck Stringer Plate, breadth and thickness	50	5
" " Angles on Upper Edge								" Angle on ditto	3 x 3	6
" " Spacing		40				40		" Tie Plates, outside Hatchways	7	7
BEAMS, Lower Deck, Single Angle, Bulb Angle, Plate or Tee Bulb								" Diagonal Tie Plates on Bms., No. of Pairs		
" " Angles on Upper Edge								" Main Dk* Iron or Steel for lng.		
" " Spacing								" R. Q. Dk* Iron or Steel for lng.	7/20	7/20
BEAMS, Hold, Plate or Tee Bulb								" Wood Deck, Material & thickness	3	3
" " Angles on Upper Edge								Lower Deck Stringer Plate, breadth and thickness		
" " Spacing								" Angles on ditto, No.		
BEAMS, Poop Deck, Angle, Bulb Angle, Plate or Tee Bulb								" Tie Plates, outside Hatchways		
" " Angles on Upper Edge								" Deck* Material and thickness		
" " Spacing								Hold Stringer Plate		
BEAMS, Bridge or Pt. Awng. Deck, Angle, Bulb Angle, Plate, or Tee Bulb								" Angles on ditto, No.		
" " Angles on Upper Edge								Poop Deck Stringer Plate, breadth & thickness		
" " Spacing								" Angle on ditto		
BEAMS, Forecastle Deck, Angle, Bulb Angle, Plate or Tee Bulb		3	2 1/2	5	3	2 1/2	5	" Tie Plates		
" " Angles on Upper Edge								" Deck, Material and thickness		
" " Spacing		31				31		Bridge or Pt. Awning Deck Stringer Plate, breadth and thickness		
PILLARS, In 'tween Decks, Size and Spacing								" Angle on ditto		
" " Hold		2 1/2	as arranged					" Tie Plates		
" " Quarter, 'tween Dks.,								" Deck, Material and thickness		
" " in Hold								Forecastle Deck Stringer Plate, brdth & thcknss	5	5
WEB FRAMES, In Fore Body, No. and Spacing								" Angle on ditto		
" " Brdth. & Thickness								" Tie Plates		
" " No. of Side Stringers								" Deck, Material and thickness		
WEB FRAMES, In E. & B. Space, No. & Spacing								Are the outside Plates doubled two spaces of Frames in length?		

