

(LLOYDS REGISTER.)

G. R. 130
Lloyds.

VESSELS OF 100 TONS AND UPWARDS.

These particulars are supplied by the Registrar General of Shipping and Seamen for the sole use of Lloyds Register of British and Foreign Shipping.

Signal Letters (if any) *H. J. Q. M.*

Official Number.		Name of Ship.		No., Date, and Port of Registry.	
123295.		<i>Myton</i>		<i>93/1906 Hull</i>	
No., Date, and Port of Previous Registry (if any).					
Whether British or Foreign Built.	Whether a Sailing or Steam Ship; and if a Steam Ship how propelled.	Where Built.	When Built.	Name and Address of Builders.	
<i>British</i>	<i>Steam Screw</i>	<i>Hull</i>	<i>1906</i>	<i>Charles Shipbuilding & Engineering Co. Ltd. Hull</i>	
Number of Decks	<i>One</i>	Length from fore part of stem, under the bowsprit, to the aft side of the head of the stern post		Feet.	Tenths.
Number of Masts	<i>Two</i>	Length at quarter of depth from top of weather deck at side amidships to bottom of keel		<i>135</i>	—
Rigged	<i>Ketch</i>	Main breadth to outside of plank		<i>22</i>	<i>6</i>
Stern	<i>Elliptic</i>	Depth in hold from tonnage deck to ceiling at midships		<i>12</i>	<i>34</i>
Build	<i>Plinches</i>	Depth in hold from upper deck to ceiling at midships, in the case of three decks and upwards		—	—
Galleries	—	Depth from top of beam amidships to top of keel		—	—
Head	—	Depth from top of deck at side amidships to bottom of keel		—	—
Framework and description of vessel	<i>Steel Trawler</i>	Round of beam		—	<i>5</i>
Number of Bulkheads	<i>Four</i>	Length of engine room (if any)		<i>31</i>	<i>7</i>
Number of water ballast tanks, and their capacity in tons	—				

PARTICULARS OF DISPLACEMENT.

Total to quarter the depth from weather deck } at side amidships to bottom of keel ... }	tons.	Ditto per inch immersion at same } depth ... }	tons.
---------------------------------------------------------------------------------------------	-------	---------------------------------------------------	-------

PARTICULARS OF ENGINES (if any).


No. of Engines.	Description.	Whether British or Foreign made.	When made.	Name and Address of Makers.	No. of and Diameter of Cylinders.	Length of Stroke.	N. H. P. I. H. P. Speed of Ship.
<i>One</i>	<i>Reciprocating triple expansion surface condensing</i>	<i>British</i>	<i>1906</i>	<i>Charles Shipbuilding & Engineering Co. Ltd. Hull</i>	<i>Three</i>	<i>24"</i>	<i>44.5</i>
<i>set.</i>	<i>Number... One... Iron or Steel... Pressure when loaded... 200</i>		<i>1906</i>		<i>Boilers.</i>		<i>22"</i>
					<i>36"</i>		<i>10 1/2 knots</i>

PARTICULARS OF TONNAGE.

GROSS TONNAGE.		No of Tons.	DEDUCTIONS ALLOWED.		No. of Tons.
Under Tonnage Deck	...	<i>256.45</i>	On account of space required for propelling power		<i>142.29</i>
Closed-in spaces above the Tonnage Deck, if any	...		On account of spaces occupied by Seamen or Apprentices, and appropriated to their use, and kept free from goods or stores of every kind, not being the personal property of the Crew		
Space or spaces between Decks	...	<i>14.82</i>	These spaces are the following, viz.:-		
Poop	<i>Break</i>		<i>Ycb scabin</i>		<i>22.69</i>
Forecastle	...	<i>5.60</i>	Deductions under Section 79 of the Merchant Shipping Act, 1894, as follows:-		
Round House	...		Cubic Metres		
Other closed-in spaces, if any, as follows:-	...		<i>Master 16.4</i>		
Spaces for machinery, and light, and air, under Section 78 (2) of the Merchant Shipping Act, 1894, if required.	...	<i>10.90</i>	<i>Chart Room 3.50</i>		<i>8.64</i>
Gross Tonnage	...	<i>284.77</i>	<i>Boon's Store 3.50</i>		
Deductions, as per Contra	...	<i>173.62</i>	Total Deductions	<i>173.62</i>	
Registered Tonnage	...	<i>114.15</i>			

Name of Master	Certificate of { Service No. Competency No.
No. of Owners	
Name, Residence, and Description of Managing Owner if there are more owners than one.	
<i>The City Steam Fishing Co Ltd of the City and County of Kingston upon Hull</i>	
<i>John Arthur Laverack, St Andrew Dock, Hull; Manager</i>	

Dated *19 November 1906.*



Re
5
M
Eng
Boi
Reg
Non
EN
Di
Is
in
bet
line
Di
col
N
N
A
I
B
each box
W
Pit
Mate
Mate
Diam
Thickn
Diameter
Pitch acr
thickness of
Working pr
separately
holes
If stiffened wit