

S.S. Ikeda *Wab report No. 9686.*

PARTICULARS OF LONGITUDINAL FRAMING.

FRAMING.	AMIDSHIPS.			ENDS.			AMIDSHIPS.			ENDS.			RIVETING.				
	In Ship.			In Ship.			Per Rule or as approved.			Per Rule or as approved.			Rivets in Longitudinal Frames. Diam. Speng.	Spacing of Rivets on each side of Transverses and Bulkheads.	Rivets in Brackets to Bulkheads.		
	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Inches.			Number.	Diameter. Inches.	
or E	6½	3½	.4	6½	3½	.36	6½	3½	.4	6½	3½	.36	7/8	5¼	✓	7	7/8
Between Decks ...	"	"	"	"	"	"	"	"	"	"	"	"	"	"	✓	"	"
Farthest Continuous No. 1	7	"	"	7	"	"	7	"	"	7	"	"	"	"	✓	"	"
" 2	"	"	"	"	"	"	"	"	"	"	"	"	"	"	✓	"	"
" 3	7½	3½	.42	7	3½	.42	7½	3½	.42	7	3½	.42	"	"	5 dia: 10 Rivets	8	"
" 4	8	"	"	7½	"	"	8	"	"	7½	"	"	"	"	✓	"	"
" 5	8½	"	"	8	"	"	8½	"	"	8	"	"	"	"	✓	9	"
" 6	9	"	.44	8½	"	.44	9	"	.44	8½	"	.44	"	"	✓	"	"
" 7	9½	"	"	9	"	"	9½	"	"	9	"	"	"	4¾	4 dia: 10 Rivets	10	"
" 8	10	"	.46	9½	"	.46	10	"	.46	9½	"	.46	"	"	✓	"	"
" 9	"	"	.56	10	"	.52	"	"	.56	10	"	.52	"	"	✓	"	"
" 10																	
" 11																	
" 12																	
" 13																	
" 14																	
" 15																	
" 16																	
Amidships	30						30										
At Ends	22/30						22/30										
Top Longitudinals	7½	3	.4	7	3	.4	7½	3	.4	7	3	.4	7/8	5¼			
Bottom "	8	3½	.4	7½	3½	.4	8	3½	.4	7½	3½	.4	"	"			
Longitudinals	30																
	21/30																
Transverses.													Rivets in Lugs to Shell Diam. Speng.				
Depth and Thickness	"																
Face Angles	"																
Lugs to Shell*	"																
Depth and Thickness	15		.38	15		.38	15		.38	15		.38					
Face Angles	5	3½	.46	5	3½	.46	5	3½	.46	5	3½	.46					
Lugs to Shell*	3½	3½	.38	3½	3½	.38	3½	3½	.38	3½	3½	.38	7/8	5 dia Jagged			
Depth and Thickness	28	✓	.5	33/37	.5		28	.5	33/37	.5							
Face Angles	9	3½	.72	9	3½	.72	9	3½	.72	9	3½	.72					
Lugs to Shell*	6	6	.46	6	6	.46	6	6	.46	6	6	.46	"	" Jagged			
Brackets	8	3½	.4	8	3½	.4	8	3½	.4	8	3½	.4					
Transverse Frames	11	14					11	14									
Angled or Liners.																	
Bridge Deck ...	✓												Spacing.			In Ships.	As approved.
Awg. or Shltr. Dk.	6	3	.38	6	3	.34	6	3	.38	6	3	.34	36/40	Transverse	11x38 8½x3½x62	11x38 8½x3½x62	
Upper "	7½	3	.4	7	3	.4	7½	3	.4	7	3	.4	37½/40	Beams.	14x44 9x3½x72	14x44 9x3½x72	
Second "	✓																
Third "	✓																

Parts of framing in peaks (if ordinary), Floors, Centre Girder, Side Girders and Margin Plate and their angle attachments, etc., to be entered in their respective places provided for on the Report Forms.

NOTE:—This slip to be pasted on the fourth page of the Report, and reference to same to be made under framing, etc., on the first page.

W872-0013