

(Recd  
 T of SURVEY  
 19.....When handed in at Local Office.....25 NO  
 3

1885

Is Certificate required? If so, to be sent to.



Lloyd's Register  
Foundation

W 883 - 0/23 1/2



STEEL S.S. JOHN MILES

5 STRAKE to 27 pairs in place.

F. STAKE No 1 renewed. No 2 removed. Jaws and split

8 frames removed from peak tank to top to deck. 3 more frames removed. 7 frames jacked in place. One beam cropped and part removed. One beam knee removed.

One forecastle stringer plate renewed. one stringer angle renewed  
one waterway bar renewed. The wood deck on forecastle was part  
renewed. The windlass was opened out for examination.

One painting stinger plate and one bulkhead plate were joined in place. One length of precast concrete bonding removed.

One house pipe renewed. One stockless anchor and 15 fathoms of cable renewed. (For particulars see Log of repairs) On the completion of these repairs - the fire peak was tested and found satisfactory Damage (2). STAG. SIDE D.

One skull plate in E. SPRAKE No 6 from app removed joint and  
replied. One skull head frame part removed.

One bulbhead plate part removed. 3 frames fixed in place

One bullhead basket removed. Fair and settled

3 shell has removed. Jarid and ypted

L. A. A. A.

When Anchors or Cables are supplied, the particulars are to be reported in the following form:—

EQUIPMENT LETTER

ANCHORS.

Number of Certificate.	Anchor.*	WEIGHT, EY. SPOCK.	WEIGHT OF SPOCK.	TEST, PER CERTIFICATE.	WEIGHT REQUIRED by TABLE 50 or 51.	Description of Anchor.	Makers.	Where and when tested and Superintendent.
		Cwts. qrs. lbs.	Cwts. qrs. lbs.	Tons. Cwts. qrs. lbs.	Cwts. qrs. lbs.			
20475	1st Bower ...	15 0 21	150000	16 14 1 14	14 2 0	"Bapt" Bower	W. J. J. J.	So. 17-4-16. L. H. H.
	2nd "							
	3rd "							
	Collector Weight.							
	Stream .....							
	Kedge.....							

\* When a bower anchor is supplied it must be clearly stated whether it is a 1st, 2nd, or 3rd bower.

## CHAIN CABLES.

[illegible]

*L. A. Howard*