

1 or 2 Dks., R. Q. Dk.,
and Pt. Awng. Dk.

IRON OR STEEL STEAMER.

No. 17326

State of Report is also sent on the Machinery of the Vessel
Date of completion of Report 14th November 1905.
Date, First Survey June 26th

Received at London Office, 16 NOV 1905
Port of Hull.
Last Survey Nov 8th 1905
Rig Ketch.

Survey held at Hull.

On the Steam Trawler "DAUNTLESS."

TONNAGE under
Tonnage Deck... 235.85
Do. of Poop
Do. of Raised Or. 14.30
Dk. or Break...
Do. of Bridge House
Do. of Forecastle
Do. of Houses on Deck 5.12
Do. of excess of Hatchways
Do. above Crown of
Engine Room... 10.59
Gross Tonnage 265.89
Less Crew Space 23.84
Less above Crown of
Engine Room... 10.59
TONNAGE FOR FEES... 231.46
Less Engine Room 133.86
Less Navigation Spaces 9.27
+ Above Crown of Engine Room 10.59
Register Tonnage 99.92
as cut on Beam...

ONE OR TWO DECKED VESSEL.

CLASS 100A1 "Steam Trawler"

Half Breadth (moulded) 11.04
Depth from upper part of Keel to top of Main Deck Bms. 13.33
Girth of Half Midship Frame (as per Rule) 20.16
1st Number 44.53
Length on deck from after part of stem to fore part of stern post 128.792
2nd Number 54.35
Proportions—Breadths to Length 5.83
Depths to Length—Main Deck to top of Keel 9.64

Master

Year of appointment (1) As master in service of owner of present vessel: 19
(2) As master of this vessel: 19

Built at Hull.

When built 1905 Launched 11th October.

By whom built Carlisle Shipbuilding & Engineering Co. Ltd.

Owners J. Hollingworth.

Managers

(Where necessary to be entered in Reg. Book).

Residence Hull.

Port belonging to Hull.

Destined Voyage Fishing

Surveyed while Building, Afloat, & in Dry Dock Yes

as cut on Beam ...		Feet.		Inches.		Feet.		Inches.		Feet.		Inches.		No. of Decks with Flat laid		One							
LENGTH on Deck as		128		9 1/2		BREADTH—		22		1		DEPTH, ACTUAL—		12		0		No. of Tiers of Beams		One			
per Rule.....						Moulded						Top of Floors to top of Main											
												Deck Beams											
of Ship on Register Length		130.0		breadth.		22.25		depth.		11.87		Moulded Depth,		12		ft. 10		ins.		Round of Beam, Actual		6	

Dimensions of Ship per Register, Length, 130.0 breadth, 22.25 depth, 11.87 Moulded Depth, 12 ft. 10 ins. Round of Beam, Actual 6 ins.

FRAMING.	Inches in Ship.	Inches in Ship.	16ths of 30ths in Ship.	Inches per Rule Or as Approved.	16ths of 30ths in Ship.	Inches per Rule Or as Approved.	FORGINGS AND CASTINGS.	Inches in Ship.	Inches per Rule Or as Approved.
FRAME, Angles, 7.5 or 8.0, for 1/2 length amidships	4 1/2	3	20	4 1/2	3	20	KEEL, Bar or Side Plates depth and thickness	8 x 2	8 x 2
Do. for 1/2 at each end	4 1/2	3	20	4 1/2	3	20	STEM, moulding and thickness	8 x 2	8 x 2
Do. in way of Double Bottoms at Solid Floors							STERN-POST for Rudder do. do.	6 1/2 x 3 1/2	6 1/2 x 3 1/2
Do. in way of Double Bottoms at Solid Floors							for Propeller	4 1/2	4 1/2
Spacing of Frames from centre to centre	20			20			MAIN PIECE of Rudder, diameter at head	3 1/2 x 3	3 x 2 1/2
REVERSED FRAME, Angles in 1/2 length amidships	3	3	6	3	3	6	RUDDER, how constructed	Forged iron frame, plated.	
DEPTH FRAMING, depth of girder	4 1/2			4 1/2			Can the Rudder be unshipped afloat?	Yes	
FLOORS, depth and thickness of Floor Plate at mid-line for 1/2 length amidships	16			16			KEELSONS AND STRINGERS.	Inches in Ship.	Inches per Rule Or as Approved.
Do. in way of Engines and Boilers	E 7.08			7.8			CENTRE LINE KEELSON, Vertical Plate above floors, Through Plate, or Intercoastal Plate	8 1/2	8 1/2
Thickness at the ends of vessel							Do. Rider Plate		
Depth at 1/2 the half breadth, as per Rule							Bulb Plate to Intercoastal Keelson		
Height extended at the Bilges							Horizontal Plates on Floors		
FLOORS & BRACKETS, in Cell Dble Bottoms							Angles	5	3
Do. state if flanged (top & bottom)							SIDE KEELSON, Angles		
Spacing							Bulb or Plate above floors for lng.		
CENTRE GIRDER, in Double Bottom, depth and thickness							Intercoastal Plate for length		
Angles, Top							Attached to outside plating with Angle		
Bottom							BILGE KEELSON, Angles (1.0 in.)	5	3
SIDE GIRDERS, number on each side & thickness							Bulb or Plate above floors for lng.		
Do. state if flanged (top & bottom)							Intercoastal Plate for length		
Angles							Attached to outside plating with Angle		
MARGIN PLATE, depth (exclusive of flange) and thickness							BILGE STRINGER Angles (1.0 in.)	5	3
Angles to Outside Plating							Bulb Plate for length		
Floors							Intercoastal Plate for length		
Height of Floors at the Bilges							Attached to outside plating with Angle		
INNER BOTTOM PLATING, breadth and thickness of Middle Line Strake							SIDE STRINGER Angles (1.0 in.)	5	3
Thickness in Engine and Boiler space							Bulb or Intercoastal Plate for lng.		
Remainder in Holds							Attached to outside plating with Angle		
BEAMS, Main and Raised Quarter Deck, Single Angle, Bulb Angle, Plate or Tee Bulb	5	3	8	5	3	8	Main and Raised Quarter Deck Stringer Plate, breadth and thickness	26	6
Angles on Upper Edge							Angle on ditto	3 x 3	6
Spacing	40			40			Tie Plates, outside Hatchways	7	6
BEAMS, Lower Deck, Single Angle, Bulb Angle, Plate or Tee Bulb							Diagonal Tie Plates on Bms., No. of Pairs		
Angles on Upper Edge							Main Dk* Iron or Steel for lng.		
Spacing							R. Q. Dk* Iron or Steel for lng.	5	5
BEAMS, Hold, Plate or Tee Bulb							Wood Deck, Material & thickness	3	3
Angles on Upper Edge							Lower Deck Stringer Plate, breadth and thickness		
Spacing							Angles on ditto, No.		
BEAMS, Poop Deck, Angle, Bulb Angle, Plate or Tee Bulb							Tie Plates, outside Hatchways		
Angles on Upper Edge							Deck* Material and thickness		
Spacing							HOLD STRINGER PLATE		
BEAMS, Bridge or Pt. Awng. Deck, Angle, Bulb Angle, Plate, or Tee Bulb							Angles on ditto, No.		
Angles on Upper Edge							POOP DECK STRINGER PLATE, breadth & thickness		
Spacing							Angle on ditto		
BEAMS, Forecastle Deck, Angle, Bulb Angle, Plate or Tee Bulb	4	3	6	4	3	6	Tie Plates		
Angles on Upper Edge							Deck, Material and thickness		
Spacing	20			20			Bridge or Pt. Awng. Deck Stringer Plate, breadth and thickness		
PILLARS, In 'tween Decks, Size and Spacing							Angle on ditto		
Hold							Tie Plates		
Quarter, 'tween Dks.,	2 1/2			As arranged			Deck, Material and thickness		
in Hold							Forecastle Deck Stringer Plate, brdth & thcknss	5	5
WEB FRAMES, In Fore Body, No. and Spacing							Angle on ditto		
No. of Side Stringers							Tie Plates	5	5
WEB FRAMES, In E. & B. Space, No. & Spacing							Deck, Material and thickness		
Brdth. & Thickness							Are the outside Plates doubled two spaces of Frames in length?	Yes	
WEB FRAMES, In After Body, No. and Spacing							Are the Sluice Valves and Watertight Doors in efficient working order?	Yes	
Brdth. & Thickness									
No. of Side Stringers									
Size of Angles or Tee Bars to Web Frames									
BRACKET PLATES to Stringers between Web Frames, Depth and Thickness									

