

GEORGE CLARK, LIM.
SOUTHWICK ENGINE WORKS,
SUNDERLAND.

WORKING PRESSURE 130 LBS PER SQ INCH TEST PRESSURE 500 LBS PER SQ INCH TO BOARD OF TRADE & LLOYDS REG

ALL PLATES, RIVETS &	STAYS OF STEEL, LAP WELDED IRON TUBES
ALL HOLES TO BE DRILLED IN POSITION	
TENSILE STRENGTH OF SHELL PLATES & BUTTSTRAPS TO BE NOT LESS THAN 28½ & NOT MORE THAN 32 TONS PER SQ INCH	
OTHER	26
LONGITUDINAL STAYS & GIRDERS	32
RIVETS & SCREW STAYS	27
THE ELONGATION OF SHELL PLATES, BUTTSTRAPS & GIRDERS & LONGITUDINAL STAYS TO BE NOT LESS THAN 20% IN A LENGTH OF INCHES	
OTHER	23%
RIVETS	25%
SCREW STAYS	25%



GIRDER STAYS.		
Nº OF	DIA.	LENGTH
81	1 3/4"	1'-4 1/2"



J.R.R.
2.4.10

—BOILERS N^o 932.—

SECTION ON LINE C.D


932

G. CLARK L^A M. BOILERS.

30 OFF FOR. 180 LBS

SIR J LAING & SONS L^A

S.S. N^o 630



LLOYDS TEST
N^o 2852
360 LBS
29-4-10 W.B.

S. S. Mmona

Sld. Rpt. no. 24630

W 97-0054

© 2019

Lloyd's Register
Foundation

J.F.S.
1.4.10.