

Room ...)
Tonnage 3681.40
Space 119.04

Depth "d," at middle of length (See Secs. 2 & 13) 16.1

Managers

(Where necessary to be entered in Reg. Bo

Residence Shell A

Lon

in Dr

No. 0

No. 0

e Dk. R

r Dk. D

Inch
Size
Ship

ing 2718

2914

3378

572

Inches
in Ship

ove)
late)

.....

.....

.....

.....

.....

.....

.....

length

gle ...

.....

length

gle ...

.....

.....

length ...

le.....

.....

.....

kness

ridge)

kness

ridge)

lge) ... 46

ays.....

l lng. ✓

.....

e)

thickness

46

.....

.....

all lng. ✓

.....

.....

Ship Surveyor 23.5.14

Received from Chief Ship Surveyor

NAME Steel m/s. "Arum" Rpt. Nwe No. 6617

Orders of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/92.)

by

It is submitted before this case receives the consideration of the Committee, the Newcastle Surveyors should be written to and asked to state by wire whether they are correct in reporting the butts of the 2nd strake below the sheer as double riveted in view of the breadth of the strake shewn in the section as built, and the amendment in Red on the approved section.

M. Wood

23.5.14.

E. E. E.

5.14



© 2020

Lloyd's Register
Foundation

W970-0052

Brackets at intermdt. ring, with thickness	22	22	46	46	46	Deck. Iron or steel	full lng.
Height of Outside Brackets above at bilge	22	22	46	46	46	Wood Deck. Material & thickness	
ER BOTTOM PLATING, breadth and	46	46	46	46	46		