









GENERAL REMARKS—(continued).

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 105.5 ft., R.Q.D.        ft., Bridge 52.0 ft., Forecastle 40.0 ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated.

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as should appear in the Register Book) 2 decks - steel. & web frames.  
 Official No. 213909; Signal Letters LFSV State if Machinery is fitted aft yes  
 How are the surfaces preserved from oxidation? Inside (Paint, except in cargo tanks. Asp. in double bottom.) Outside Paint.

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors. cellular sys

Where Fitted.	*Length. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. Feet.	Water Capa. Tons.
Double bottom, aft,			Fore peak tank,		100
Double bottom, under Engines and Boilers, <u>aft</u>	<u>61.5</u>	<u>201</u>	After peak tank,		74
Double bottom, if under Engines only,			Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,		
Double bottom, forward,	<u>56.6</u>	<u>232</u>	Other tanks, if fitted,		
	Total capacity of double bottom	<u>433</u>	(If necessary, furnish further information by sketch.)		

\* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules. yes

Order for Special Survey No. 7

Date June 1915

No. 122 in builder's yard.

DATES of Surveys held while building

Aug. 26 Sept. 15-30 Oct. 1-4-11-14-16-18-19-20-24-27-30 Nov. 1-5-8-18-19-24-27-29-30 Dec. 1-4-6-7-8-10-14-15-16-17-18-27-30 1915. Jan. 3-4-13-14-15-19-20-25-26-31-Feb. 4-7-8-14-17-21-24-25 Mar. 2-3-4-5-7-8 1916.

Surveyor's Signature



## PARTICULARS OF LONGITUDINAL FRAMING.

SFo.Rpt.

No.2298.

FRAMING.		AMIDSHIPS.			ENDS.			AMIDSHIPS.			ENDS.			RIVETING.				
		In Ship.			In Ship.			Per Rule or as approved.			Per Rule or as approved.			Rivets in Longitudinal Frames. Diam. Speng.	Spacing of Rivets on each side of Transverses and Bulkheads. Inches.	Rivets in Brackets to Bulkheads.		
		Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.			Number.	Diameter. Inches.	
V, L or E .....																		
Bridge 'tween Decks ...		6	3	.375	6	3	.375	6	3	.375	6	3	.375					
Uppermost Continuous?		8	3½	.406	8	3½	.406	8	3½	.406	8	3½	.406	7/8	5½	5½" throughout	12	7/8
No. 1																		
" 2		"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
" 3		"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
" 4		9	3½	.438	9	3½	.438	9	3½	.438	9	3½	.438	"	"	"	"	"
" 5		"	"	"	"	"	"	"	"	"	"	"	"	"	3 15/16"	11-spces.	14	"
" 6		10	3½	.484	10	3½	.484	10	3½	.484	"	"	"	"	"	"	"	"
" 7		"	"	"	10	3½	.484	"	"	"	10	3½	.484	"	"	"	"	"
" 8		"	"	"	"	"	"	"	"	"	"	"	"	3 1/16"	"	"	"	"
" 9		10	3½	.625	"	"	"	"	"	.625	"	"	"	"	"	"	16	"
" 10		12	3	.773	.473			12	3	.773	.473			"	"	"	"	"
" 11		12	3	.895	.595			"	3	.895	.595			"	"	"	20	"
" 12		"	3	.773	.473			"	3	.773	.473			"	"	"	"	"
" 13		"	4	.70				"	4	.70				3 15/16"	"	"	16	"
" 14														"	"	"	"	"
" 15														✓	"	"		
" 16															do. do. in			
Amidships 30"															Longs.up to			
At Ends various															No.22			
Tank Top Longitudinals					7	3	.438	✓			7	3	.438			These in double bottoms		
Bottom "					8	3½	.406	✓			8	3½	.406			forward.		
Longitudinals { Amidships																		
At Ends 27"																		
Transverses.														Rivets in Lugs to Shell Diam. Speng.				
{ Depth and Thickness		14	✓	.40					14	.40								
{ Face Angles		4	3½	.44					4	3½	.44							
{ Lugs to Shell*		3½	3½	.40					3½	3½	.40			7/8	3 15/16			
{ Depth and Thickness		18	✓	.40					18	.40				"	"			
{ Face Angles		4	3½	.44					4	3½	.44							
{ Lugs to Shell* yes..		3½	3½	.40					3½	3½	.40			"	"			
{ Depth and Thickness		34	✓	.46					34	.46								
{ Face Angles		10	3½	.625	BA				10	3½	.625	BA						
{ Lugs to Shell*		6	6	.50					6	6	.50			7/8	4½"	double rivetting.		
{ Brackets		.46	to .40	flanged	.46	to .40	flanged		.46	to .40	flanged							
Transverse Frames		9'6"	✓		9'6"													
if joggled or liners.																		
Bridge Deck ...		6	3	.375					6	3	.375			Spacing.		Plates & Angles		
Awg.or Shltr.Dk.																In Ships. and As approved.		
Upper "		7	3	.438					7	3	.438	30"				Plate. Angles	Plate. Angles	
Second "		8	3½	.406					8	3½	.406	30"				11x.40	3x3x.38	
Third "																3x3x.375		
																11x.40	3½x3½x.40	
																18x.40	6x4x.50	
																20x.40	6x6x.44	
																9x3½x.438		

Particulars of framing in peaks (if ordinary), Floors, Centre Girder, Side Girders and Margin Plate and their angle attachments, etc., to be entered in their respective places provided for on the Report Forms.

NOTE:—This slip to be pasted on the fourth page of the Report, and reference to same to be made under framing, etc., on the first page.

W982-01753/3