

URGENT CASE

W987-0217

PUMPING ARRANGEMENT Endorsement.

Shipbuilders: Messrs.

Schoeps Rieden J. Koste Agyu Yard No. 161/2

Engineers: Messrs.

Engine No.

Owners: Messrs.

It is submitted that the plans of

General

Pumping Arrangement *a Compressed Air Fuel oil Lubricating oil
Piping Arrangement*

merit approval, provided the arrangements be as

shown and amended on the plan and the remaining

requirements of Sections 20 and 34 of the Rules (1937-8)

be complied with so far as they are applicable.

It is noted that the power pumps connected to the main bilge line consist of one centrifugal pump of 50 tons/hr capacity and one main engine driven bilge pump, and the Surveyor should be asked to state the capacity of the latter pump in view of the requirements of Section 34 clause 7(b) of the Rules.

It should be added that the size of the connection from the centrifugal pumps to the main bilge line should be in any case not less than that required for the main bilge line, and if the capacity of the main engine driven bilge pump is only suitable for a *large* suction pipe than 2" bore, the connection from the centrifugal pumps should be not less than 2½" bore.

Return plan.

Retain copy.

E. 4. 2m, 8, 36. T.

Lo 22/p



© 2019
Lloyd's Register
Foundation
*R.B.
21/2/38*