Dimensions of Ship per Register, Length 404·3 breadth 52·25 depth 27·45. Moulded depth, ft. 38 ins. 0 / To Bridge Dk. Moulded depth, ft. 30 ins. 0 / To Upper Dk. Round of Dk. Beam

FRAMING. | Inches in Ship. | Inches in Ship. | Inches in Ship. | Inches per Rule | Inches per Rule | Inches per Rule | PILLARS | Inches. Size in Ship. | Inches Spacing in Ship.

COPY.

Turner & Co.

The Asiatic Steam Navigation Co., Ld.
45 St Mary Axe,
London, E.C. 3.

12th January 1922.

Messrs Lithgows Limited,
Kingston Shipbuilding Yard,
Port-Glasgow.

Dear Sirs,

No. 742 - S. S. "Kohinur".

Please note that we wish the above vessel to have Five Watertight Bulkheads extending to Upper Deck and One on the after part of the vessel extending to the Second Deck. This arrangement we require to suit the trade for which the vessel is intended to run.

Yours faithfully,
(Signed) Turner & Co.,
Managers.

© 2019 Lloyd's Register Foundation

" Angles on upper edge ..... ✓ ✓ " Angle on ditto ..... 3½ x 3½ x

" Spacing ..... 26 26 " Tie Plates ..... -

BEAMS, Forecastle Deck, ~~Angle~~, Bulb Angle, 9½ 3½ ·52 9½ 3½ ·52 " Deck. Material and thickness Steel