

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Received at London Office 10 APR 1929

Date of writing Report 26.3.29 When handed in at Local Office 6.4.29 Port of GLASGOW.

No. in Survey held at TRON. Date, First Survey 22.3.28 Last Survey 28/3/1929.
 Reg. Book. (Number of Visits.....)

on the S.S. THE VICEROY Tons { Gross 561
 Net 824

Built at TRON By whom built MESSRS THE HILSHSBCO Yard No. 404 When built 1929.

Owners MESSRS J. HAY & SONS LTD. Port belonging to GLASGOW.

Electric Light Installation fitted by MESSRS CLAUD HAMILTON LTD Contract No. 404 When fitted 1929.

System of Distribution Double wire distributing fuse box.

Pressure of supply for Lighting 110 volts, Heating none volts, Power none volts.

Direct or Alternating Current, Lighting direct Power none

If alternating current system, state frequency of periods per second -

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off Yes.

Generators, do they comply with the requirements regarding overload Yes., are they compound wound Yes.
 are they over compounded 5 per cent. Yes., if not compound wound state distance between each generator -

Where more than one generator is fitted are they arranged to run in parallel one only., is an adjustable regulating resistance fitted in series with each shunt field Yes.

Are all terminals accessible and clearly marked Yes., are they so spaced or shielded that they cannot be accidentally earthed, or short circuited Yes. Are the lubricating arrangements of the generators as per Rule 5 Sect 2 Yes.

Position of Generator Engine Room, is the ventilation in way of the generators satisfactory Yes., are they clear of all inflammable material Yes.
 if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators none and -, are the generators protected from mechanical injury and damage from water, steam or oil -

are their axis of rotation fore and aft Yes.

Earthing, are the bedplates and frames of the generating plant efficiently earthed Yes. are the prime movers and their respective generators in metallic contact Yes.

Main Switch Boards, where placed Engine Room
 If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard Same compartment

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes Yes.
 are they protected from mechanical injury and damage from water, steam or oil Yes., if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards none and -, are they constructed wholly of durable, incombustible non-absorbent materials Yes., is all insulation of high dielectric strength and of permanently high insulation resistance Yes., if semi-insulating material is used, are all conducting parts connected to one pole insulated from the slab with mica or micaite and the slab similarly insulated from its framework Yes., and is the frame effectively earthed Yes. Are the following fittings as per Rule, viz.:— spacing or shielding of live parts Yes., accessibility of all parts Yes., absence of fuses on back of board Yes., proportion of omnibus bars Yes., individual fuses to voltmeter, pilot or earth lamp Yes., connections of switches Yes.

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches
D.P. main switch and fuse for dynamo and S.P. Switches and D.P. fuses for each out going circuit

Instruments on main switchboard 1 ammeters 1 voltmeters - synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system lamp lamp.

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules Yes.

Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule 3 Sect 6



© 2020

Lloyd's Register Foundation

W991-0053

Insulation of Cables, state type of cables, single or twin main twin are the cables insulated and protected as per Tables III or IV of the Rules yes
strand wiring single
Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load 5 Volts
Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.007 square inch and above provided with soldering sockets yes
Paper Insulated Cables, If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound no paper
Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage yes
Support and Protection of Cables, state how the cables are supported and protected Lead covered only and lead covered in tubing clipped to under decks and bulk heads
If cables are run in wood casings, are the casings and caps secured by screws, are the cap screws of brass, are the cables run in separate grooves, If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VI yes
Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements none
Joints in Cables, state if any, and how made, insulated, and protected no joints
Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands yes
Bushes in Beams and Non-watertight Positions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed yes state the material of which the bushes are made lead
Earthing Connections, state what earthing connections are fitted and their respective sectional areas, are their connections made as per Rule
Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule yes
Emergency Supply, state position and method of control of the emergency supply and how the generator is driven none
Navigation Lamps, are these separately wired yes, controlled by separate switch and separate fuses yes
are the fuses double pole yes, are the switches and fuses grouped in a position accessible only to the officers on watch yes
has each navigation lamp an automatic indicator as per Rule yes, are separate screens provided for the use of oil and electric side lights yes
are separate oil lanterns provided for the mast head lights and side lights yes
Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight yes
are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected none
are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected no
where are the controlling switches situated
Searchlight Lamps, No. of none, whether fixed or portable, are their fittings as per Rule
Arc Lamps, other than searchlight lamps, No. of, are their live parts insulated from the frame or case, are their fittings as per Rule
Motors, are their working parts readily accessible none, are the coils self-contained and readily removable for replacement
are the brushes, brush holders, terminals and lubricating arrangements as per Rule, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material
are they protected from mechanical injury and damage from water, steam or oil, are their axis of rotation fore and aft
if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type, if not of this type, state distance of the combustible material horizontally or vertically above the motors, and
Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed as per Rule yes
Lightning Conductors, where lightning conductors are required, are these fitted as per Rule yes
Ships carrying Oil having a Flash Point less than 150 F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings
If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY.	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN	1	3	110	28	350	direct coupled to a steam engine	-	-
AUXILIARY								
EMERGENCY								
ROTARY TRANSFORMER								

LIGHTING AND HEATING CONDUCTORS.

Ref. No.	DESCRIPTION.	No. of Conductors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Ampères.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	MAIN GENERATOR	2	.01	4	.044	28	12	V.I.R.	Lead covered in tubing
	AUXILIARY GENERATOR								
	EMERGENCY GENERATOR								
	ROTARY TRANSFORMER								
	AUXILIARY SWITCHBOARDS								
	ENGINE ROOM	2	.002	3	.029	4.5	3	"	"
	BOILER ROOM								
	accommodation office	2	.003	3	.036	6	210	"	"
	Engine	2	.002	3	.029	3	50	"	"
	navigation	2	.002	3	.029	4	220	"	"
	WIRELESS								
	SEARCHLIGHT								
	MASTHEAD LIGHT	2	.002	3	.029	1	130	"	"
	SIDE LIGHTS	4	.002	3	.029	1	40	"	"
	COMPASS LIGHTS	4	.002	3	.029	.3	60	"	"
	POOP LIGHTS								
	CARGO LIGHTS								
	ARC LAMPS								
	HEATERS								

MOTOR CONDUCTORS.

Ref. No.	DESCRIPTION.	No. of Motors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Ampères.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	BALLAST PUMP								
	MAIN BILGE LINE PUMPS								
	GENERAL SERVICE PUMP								
	EMERGENCY BILGE PUMP								
	SANITARY PUMP								
	CIRC. SEA WATER PUMPS								
	CIRC. FRESH WATER PUMPS								
	AIR COMPRESSOR								
	FRESH WATER PUMP								
	ENGINE TURNING GEAR								
	ENGINE REVERSING GEAR								
	LUBRICATING OIL PUMPS								
	OIL FUEL TRANSFER PUMP								
	WINDLASS								
	WINCHES, FORWARD								
	WINCHES, AFT								
	STEERING GEAR								
	WORKSHOP MOTOR								
	VENTILATING FANS								

All Conductors are of annealed copper conforming to British Standard Specification No. 7.
 The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.
 The foregoing is a correct description.

for *Claud Hamilton & Sons* Electrical Engineers. Date *4th April 29.*
Wm. Lawrence.

COMPASSES.

Distance between electric generators or motors and standard compass *88 feet*
 Distance between electric generators or motors and steering compass *80 feet*
 The nearest cables to the compasses are as follows:—
 A cable carrying *6* Ampères *12* feet from standard compass *10* feet from steering compass.
 A cable carrying *1* Ampères *10* feet from standard compass *10* feet from steering compass.
 A cable carrying _____ Ampères _____ feet from standard compass _____ feet from steering compass.
 Have the compasses been adjusted with and without the electric installation at work at full power *yes.*
 Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted *yes.*
 The maximum deviation due to electric currents was found to be *nil* degrees on *any* course in the case of the standard compass, and *nil* degrees on *any* course in the case of the steering compass.

AILSA SHIPBUILDING CO., LIMITED

W. Stewart Secretary. Builder's Signature. Date *5th April 1929*

Is this installation a duplicate of a previous case *no.* If so, state name of vessel *✓*

General Remarks (State quality of workmanship, opinions as to class, &c.) *This installation has been fitted on board under special supervision & tested under full load conditions & found satisfactory. The materials and workmanship were found to be good and sound.*

It is submitted that this vessel is eligible for **FREE RECORD** — **ELEC. LIGHT.**

A.S.
6/4/29.

Y.R.M.
15.4.29.

Total Capacity of Generators *3* Kilowatts

The amount of Fee ... £ *5-0-0* : { When applied for, **9 APR 1929**
 Travelling Expenses (if any) £ *0/6* : { When received, *12.4.29*

J.S. Rankin.
Surveyor to Lloyd's Register of Shipping.

Committee's Minute **GLASGOW 9 APR 1929**

Assigned *Electric Light.*

Im. 921.—T. Absister. (The Surveyors are requested not to write on or below the space for Committee's Minute.)