

Register. 219.7 35.15 11.35 637.16 Moulded Depth as measured 13-5
 1-9
 11-8
 th on Frame Depth 57 Ceiling *filled* Peak

23858

Rpt. 12.

FREEBOARD VERIFICATION FORM FOR STEAMERS.

Port _____
When received in London Office
 Vessel's Name T.S.S. "SIR HARVEY ADAMSON"
 Official No. 136336 No. in Reg. Book 83181
 Port of Registry *(For Foreign Vessels)* _____
 Iron or Steel Steel State whether Classed by Lloyd's Register _____
 Name of Owners British India Ste. Nav Co. Date of Verification _____

I have to report that the Freeboard from the centre of disc to the top of the statutory deck line, and the lines in connection therewith, as given below, assigned by the Committee to this vessel, have been correctly marked on the vessel's sides, in accordance with the printed instructions:—

From centre of disc to top of statutory deck line	1	ft.	7	ins.
From centre of disc to top of statutory deck line at awning or part-awning deck	-	ft.	-	ins.
Fresh Water line above centre of disc	3		ins.	
Indian Summer line above centre of disc	2		ins.	
Winter line below centre of disc	2		ins.	
Winter North Atlantic line below centre of disc	-		ins.	
Distance between the top of statutory deck line on vessel's side and the intersection of the continuation of upper side of wood or steel deck with the vessel's side	}	at main, spar or upper dk.		1 1/2 ins.
		at awning or pt. awning dk.		ins.

NOTE.—It should be clearly shown whether the statutory deck line is set off from a wood or steel deck.

[Signature]
 17.1.27

Surveyor.

(To be filled up in London Office.)

Statement No. _____ Date of Committee's Minute _____

Particulars for record in Register Book. {
 Moulded Depth ft. ins.
 Freeboard ft. ins.
 Corresponding Draught ft. ins.

Freeboards compared and found correct by _____ Date _____

Is fee paid? _____ Form for Certificate A

Instructions _____ Date _____

Certificate written Noted for posting _____

2m, 11, 21.—T.



© 2020

Lloyd's Register Foundation

w946-0254

Fresh Water Line
 Indian Summer Line

NOT
 depth
 when
 afloat,
 of
 should
 3 1/2
 NOTE.
 round of
 should be
 ed on the
 breadth of
 at the gun